


SOT23 NPN SILICON PLANAR MEDIUM POWER TRANSISTORS

BCW65
BCW66

ISSUE 3 - AUGUST 1995

PARTMARKING DETAILS –

BCW65A – EA	BCW65AR – 4V
BCW65B – EB	BCW65BR – 5V
BCW65C – EC	BCW65CR – 6V
BCW66F – EF	BCW66FR – 7P
BCW66G – EG	BCW66GR – 5T
BCW66H – EH	BCW66HR – 7M



COMPLEMENTARY TYPES –

BCW65	–	BCW67
BCW66	–	BCW68

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	BCW65	BCW66	UNIT
Collector-Base Voltage	V_{CBO}	60	75	V
Collector-Emitter Voltage	V_{CEO}	32	45	V
Emitter-Base Voltage	V_{EBO}	5		V
Continuous Collector Current	I_C	800		mA
Peak Collector Current(10ms)	I_{CM}	1000		mA
Base Current	I_B	100		mA
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	330		mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150		$^{\circ}C$

BCW65 BCW66

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated).

PARAMETER		SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.							
Collector-Emitter Breakdown Voltage	BCW65 BCW66	$V_{(BR)CEO}$	32 45			V	$I_{CE0}=10\text{mA}$ $I_{CE0}=10\text{mA}$							
	BCW65 BCW66	$V_{(BR)CES}$	60 75			V	$I_C=10\mu\text{A}$ $I_C=10\mu\text{A}$							
Emitter-Base Breakdown Voltage		$V_{(BR)EBO}$	5			V	$I_{EBO}=10\mu\text{A}$							
Collector-Emitter Cut-off Current	BCW65	I_{CES}			20 20	nA μA	$V_{CES}=32\text{V}$ $V_{CES}=32\text{V}, T_{amb}=150^{\circ}\text{C}$							
	BCW66				20 20	nA μA	$V_{CES}=45\text{V}$ $V_{CES}=45\text{V}, T_{amb}=150^{\circ}\text{C}$							
Emitter-Base Cut-Off Current		I_{EBO}			20	nA	$V_{EBO}=4\text{V}$							
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$			0.3 0.7	V V	$I_C=100\text{mA}, I_B=10\text{mA}$ $I_C=500\text{mA}, I_B=50\text{mA}^*$							
Base-Emitter Saturation Voltage		$V_{BE(SAT)}$			2	V	$I_C=500\text{mA}, I_B=50\text{mA}^*$							
Static Forward Current Transfer	BCW65A BCW66F	h_{FE}	35 75 100 35	160	250		$I_C=100\mu\text{A}, V_{CE}=10\text{V}$ $I_C=10\text{mA}, V_{CE}=1\text{V}$ $I_C=100\text{mA}, V_{CE}=1\text{V}^*$ $I_C=500\text{mA}, V_{CE}=2\text{V}^*$							
			BCW65B BCW66G			h_{FE}	50 110 160 60	250	400	$I_C=100\mu\text{A}, V_{CE}=10\text{V}$ $I_C=10\text{mA}, V_{CE}=1\text{V}$ $I_C=100\text{mA}, V_{CE}=1\text{V}^*$ $I_C=500\text{mA}, V_{CE}=2\text{V}^*$				
							BCW65C BCW66H			h_{FE}	80 180 250 100	350	630	$I_C=100\mu\text{A}, V_{CE}=10\text{V}$ $I_C=10\text{mA}, V_{CE}=1\text{V}$ $I_C=100\text{mA}, V_{CE}=1\text{V}^*$ $I_C=500\text{mA}, V_{CE}=2\text{V}^*$
	Transition Frequency		f_T	100			MHz	$I_C=20\text{mA}, V_{CE}=10\text{V}$ $f=100\text{MHz}$						
	Collector-Base Capacitance		C_{cbo}		8	12	pF	$V_{CBO}=10\text{V}, f=1\text{MHz}$						
Emitter-Base Capacitance		C_{ebo}			80	pF	$V_{EBO}=0.5\text{V}, f=1\text{MHz}$							
Noise Figure		N		2	10	dB	$I_C=0.2\text{mA}, V_{CE}=5\text{V}$ $R_G=1\text{k}\Omega$							
Switching times: Turn-On Time Turn-Off Time		t_{on} t_{off}			100 400	ns ns	$I_C=150\text{mA}$ $I_{B1}=I_{B2}=15\text{mA}$ $R_L=150\Omega$							

Spice parameter data is available upon request for this device

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$