
ULTRA FAST RECTIFIER

UF4001 THRU UF4007

VOLTAGE RANGE **50 to 1000 Volts**
CURRENT **1.0Ampere**

DO-41



Dimensions in inches and (millimeters)

FEATURES

- Low coat construction
- Fast switching for high efficency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
  260℃/10 secods/.375”(9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.33 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25^{O}C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	UF 4001	UF 4002	UF 4003	UF 4004	UF 4005	UF 4006	UF 4007	UNITS
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V_{RMS}	35	70	140	280	420	850	700	Volts
Maximum DC Blocking Voltage		V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375”(9.5mm) lead length at T_A= 55℃		$I_{(AV)}$	1.0							Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)		I_{FSM}	30							Amps
Maximum Instantaneous Forward Voltage @ 1.0A		V_F	1.0				1.7			Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	T_A = 25℃	I_R	10							μA
	T_A = 125℃		50							
Maximum Reverse Recovery Time T_J= 25℃(NOTE 1)		trr	50				75			ns
Typical Thermal Resistance (NOTE 2)		C_J	15							PF
Typical Thermal Resistance(NOTE 3)		$R_{\theta JA}$	60							℃/W
Operating Junction Temperature Range		T_J ,T_{STG}	(-55 to +150)							℃

Notes:

1 Test Condition:IF=0.5A,IR=1.0A,IRR=0.25A

2. Measured at 1.0 MHz and applied reverse of 4.0 volts.

3 Thermal resistance from junction to ambient with .375”(9.5mm)lead length, P.C.B. mounted. .

ULTRA FAST RECTIFIER

UF4001 THRU UF4007	VOLTAGE RANGE	50 to 1000 Volts
	CURRENT	1.0Ampere

RATING AND CHRACTERISTIC CURVES UF4001 THRU UF4007

FIG.1-TYPICAL FORWARD CURRENT
DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE
CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND
REVERSE REXOVERY TIME CHARACTERISTIC



NOTE: 1.Rise Time =7ns max.Input Impedance=1megohm.22pF
2.Rise time=10ns max.Source Impedance=50 ohms