ALPHA & OMEGA SEMICONDUCTOR

AO4435

30V P-Channel MOSFET

General Description

The AO4435 uses advanced trench technology to provide excellent $R_{DS(ON)}$, and ultra-low low gate charge with a 25V gate rating. This device is suitable for use as a load switch or in PWM applications.

-RoHS Compliant
-AO4435 is Halogen Free


Product Summary


V_{DS} = -30V
I_D = -10.5A (V_{GS} = -20V)
$R_{DS(ON)}$ < 14mΩ (V_{GS} = -20V)
$R_{DS(ON)}$ < 18mΩ (V_{GS} = -10V)
$R_{DS(ON)}$ < 36mΩ (V_{GS} = -5V)

100% UIS Tested
100% Rg Tested

Green Product

SOIC-8





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current [A]	T_A=25°C	I_D	-10.5	A
	T_A=70°C		-8	
Pulsed Drain Current [B]		I_{DM}	-80	
Power Dissipation [A]	T_A=25°C	P_D	3.1	W
	T_A=70°C		2.0	
Avalanche Current [B]		I_{AR}	-20	A
Repetitive avalanche energy 0.3mH [B]		E_{AR}	60	mJ
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	32	40	°C/W
Maximum Junction-to-Ambient [A]	Steady State		60	75	°C/W
Maximum Junction-to-Lead [C]	Steady State	$R_{\theta JL}$	17	24	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D = -250∝A, V_{GS} = 0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = -30V, V_{GS} = 0V			-1	∝A
		T_J = 55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS} = 0V, V_{GS} = ±25V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS} I_D = -250∝A	-1.7	-2.3	-3	V
$I_{D(ON)}$	On state drain current	V_{GS} = -10V, V_{DS} = -5V	-80			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS} = -20V, I_D = -11A		11	14	mΩ
		T_J=125°C		15	19	
		V_{GS} = -10V, I_D = -10A		15	18	
		V_{GS} = -5V, I_D = -5A		27	36	
g_{FS}	Forward Transconductance	V_{DS} = -5V, I_D = -10A		22		S
V_{SD}	Diode Forward Voltage	I_S = -1A,V_{GS} = 0V		-0.74	-1	V
I_S	Maximum Body-Diode Continuous Current				-3.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		1130	1400	pF
C_{oss}	Output Capacitance			240		pF
C_{rss}	Reverse Transfer Capacitance			155		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	1	5.8	8	Ω
SWITCHING PARAMETERS						
$Q_{g(10V)}$	Total Gate Charge	V_{GS}=-10V, V_{DS}=-15V, I_D=-10A		18	24	nC
$Q_{g(4.5V)}$	Total Gate Charge			9.5		
Q_{gs}	Gate Source Charge			5.5		nC
Q_{gd}	Gate Drain Charge			3.3		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=1.5Ω, R_{GEN}=3Ω		8.7		ns
t_r	Turn-On Rise Time			8.5		ns
$t_{D(off)}$	Turn-Off DelayTime			18		ns
t_f	Turn-Off Fall Time			7		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-10A, dI/dt=100A/∝s		25	30	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-10A, dI/dt=100A/∝s		12		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A = 25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using <300∝s pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

F. The current rating is based on the t ≤ 10s thermal resistance rating.

G. E_{AR} and I_{AR} ratings are based on low frequency and duty cycles to keep T_j=25C.

Rev7: Nov. 2010

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)







Figure 11: Normalized Maximum Transient Thermal Impedance(Note E)


Gate Charge Test Circuit & Waveform







Resistive Switching Test Circuit & Waveforms





Unclamped Inductive Switching (UIS) Test Circuit & Waveforms





Diode Recovery Test Circuit & Waveforms

