ACT108W-600E

AC Thyristor power switch

Rev. 5 — 13 July 2010 Product data sheet

1. Product profile

1.1 General description

AC Thyristor power switch in a SOT223 surface-mountable plastic package with self-protective capabilities against low and high energy transients

1.2 Features and benefits

- Common terminal on mounting base allows multiple ACTs on shared cooling pad
- Exclusive negative gate triggering
- Full cycle AC conduction
- Remote gate separates the gate driver from the effects of the load current
- Safe clamping of low energy over-voltage transients
- Self-protective turn-on during high energy voltage transients
- Surface-mountable package
- Very high noise immunity

1.3 Applications

- Contactors, circuit breakers, valves, dispensers and door locks
- Fan motor circuits
- Lower-power highly inductive, resistive and safety loads
- Pump motor circuits

1.4 Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{DRM}	repetitive peak off-state voltage		-	-	600	V
I_{GT}	gate trigger current	V_D = 12 V; I_T = 100 mA; LD+ G-; T_j = 25 °C; see Figure 10	1	-	10	mA
		V_D = 12 V; I_T = 100 mA; LD- G-; T_j = 25 °C	1	-	10	mA
$I_{T(RMS)}$	RMS on-state current	full sine wave; T_{sp} ≤ 112 °C; see Figure 4; see Figure 1; see Figure 2	-	-	0.8	A
dV_D/dt	rate of rise of off-state voltage	V_{DM} = 402 V; T_j = 125 °C; gate open circuit; see Figure 14	1000	-	-	V/µs


Table 1. Quick reference data *...continued*

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{CL}	clamping voltage	I_{CL} = 100 µA; t_p = 1 ms; $T_j \leq 125$ °C; see Figure 17	650	-	-	V
V_{PP}	peak pulse voltage	T_j = 25 °C; non-repetitive, off-state; see Figure 3	-	-	2	kV
V_T	on-state voltage	I_T = 1.1 A; see Figure 13	-	-	1.3	V


2. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	LD	load		
2	CM	common		
3	G	gate		
4	CM	common		



SOT223 (SC-73)



001aaj924

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
ACT108W-600E	SC-73	plastic surface-mounted package with increased heatsink; 4 leads	SOT223

All information provided in this document is subject to legal disclaimers.


© NXP B.V. 2010. All rights reserved.

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DRM}	repetitive peak off-state voltage		-	600	V
$I_{T(RMS)}$	RMS on-state current	full sine wave; $T_{sp} \leq 112$ °C; see Figure 4; see Figure 1; see Figure 2	-	0.8	A
I_{TSM}	non-repetitive peak on-state current	full sine wave; $T_{j(init)} = 25$ °C; $t_p = 16.7$ ms	-	8.8	A
		full sine wave; $T_{j(init)} = 25$ °C; $t_p = 20$ ms; see Figure 5; see Figure 6	-	8	A
I^2t	I^2t for fusing	$t_p = 10$ ms; sine-wave pulse	-	0.32	A^2s
dI_T/dt	rate of rise of on-state current	$I_T = 1$ A; $I_G = 20$ mA; $dI_G/dt = 0.2$ A/µs	-	100	A/µs
I_{GM}	peak gate current	t = 20 µs	-	1	A
V_{GM}	peak gate voltage	positive applied gate voltage	-	15	V
$P_{G(AV)}$	average gate power	over any 20 ms period	-	0.1	W
T_{stg}	storage temperature		-40	150	°C
T_j	junction temperature		-	125	°C
V_{PP}	peak pulse voltage	$T_j = 25$ °C; non-repetitive, off-state; see Figure 3	-	2	kV



f = 50 Hz

$T_{sp} = 112$ °C

Fig 1. RMS on-state current as a function of surge duration; maximum values




Fig 2. RMS on-state current as a function of solder point temperature; maximum values

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.





Fig 3. Test circuit for inductive and resistive loads with conditions equivalent to IEC 61000-4-5




α = conduction angle

Fig 4. Total power dissipation as a function of RMS on-state current; maximum values


All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.



f = 50 Hz

Fig 5. Non-repetitive peak on-state current as a function of the number of sinusoidal current cycles; maximum values



$t_p \leq 20$ ms

Fig 6. Non-repetitive peak on-state current as a function of pulse width; maximum values


All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point	full cycle with heatsink compound; see Figure 9	-	-	15	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient	full cycle; printed-circuit board mounted for pad area; see Figure 7	-	70	-	K/W
		full cycle; printed-circuit board mounted for minimum footprint; see Figure 8	-	156	-	K/W




All dimensions are in mm

Printed-circuit board:

FR4 epoxy glass (1.6 mm thick), copper laminate (35 um thick),

Fig 7. Printed-circuit board pad area SOT223



All dimensions are in mm

Fig 8. Minimum footprint SOT223

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.




Fig 9. Transient thermal impedance from junction to solder point as a function of pulse width


6. Characteristics

Table 6. Characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{GT}	gate trigger current	V_D = 12 V; I_T = 100 mA; LD+ G-; T_j = 25 °C; see Figure 10	1	-	10	mA
		V_D = 12 V; I_T = 100 mA; LD- G-; T_j = 25 °C	1	-	10	mA
I_L	latching current	V_D = 12 V; I_G = 12 mA; T_j = 25 °C; see Figure 11	-	-	30	mA
I_H	holding current	V_D = 12 V; T_j = 25 °C; see Figure 12	-	9	25	mA
V_T	on-state voltage	I_T = 1.1 A; see Figure 13	-	-	1.3	V
V_{GT}	gate trigger voltage	V_D = 12 V; I_T = 100 mA; T_j ≤ 125 °C	0.15	-	-	V
		V_D = 12 V; I_T = 100 mA; T_j = 25 °C	-	-	1	V
I_D	off-state current	V_D = 600 V; T_j ≤ 125 °C	-	-	0.2	mA
		V_D = 600 V; T_j ≤ 25 °C	-	-	2	µA
dV_D/dt	rate of rise of off-state voltage	V_{DM} = 402 V; T_j = 125 °C; gate open circuit; see Figure 14	1000	-	-	V/µs
dI_{com}/dt	rate of change of commutating current	V_D = 400 V; T_j = 125 °C; $I_{T(RMS)}$ = 1 A; dV_{com}/dt = 15 V/µs; gate open circuit; see Figure 15; see Figure 16	0.3	-	-	A/ms
V_{CL}	clamping voltage	I_{CL} = 100 µA; t_p = 1 ms; T_j ≤ 125 °C; see Figure 17	650	-	-	V

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.



(1) LD+ G-

(2) LD- G-

Fig 10. Normalized gate trigger current as a function of junction temperature




Fig 11. Normalized latching current as a function of junction temperature





Fig 12. Normalized holding current as a function of junction temperature



V_O = 0.758 V; R_S = 0.263 Ω

(1)T_j = 125 °C; typical values


(2)T_j = 125 °C; maximum values

(3)T_j = 25 °C; maximum values

Fig 13. On-state current as a function of on-state voltage

All information provided in this document is subject to legal disclaimers.


© NXP B.V. 2010. All rights reserved.



A is dV_D/dt at condition T_j °C

B is dV_D/dt at condition T_j 125 °C

Fig 14. Normalized rate of rise of off-state voltage as a function of junction temperature




A is dI_{com}/dt at condition T_j °C

B is dI_{com}/dt at condition T_j 125 °C

V_D = 400 V

Fig 15. Normalized critical rate of rise of commutating current as a function of junction temperature



A[B] is dI_{com}/dt at condition B, dV_{com}/dt

A[spec] is the specified data sheet value of dI_{com}/dt

turn-off time < 20 ms

Fig 16. Normalized critical rate of change of commutating current as a function of critical rate of change of commutating voltage; minimum values





Fig 17. Normalized clamping voltage (upper limit) as a function of junction temperature; minimum values

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

7. Package outline

Plastic surface-mounted package with increased heatsink; 4 leads **SOT223**



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1	b_p	b_1	c	D	E	e	e_1	H_E	L_p	Q	v	w	y
mm	1.8 1.5	0.10 0.01	0.80 0.60	3.1 2.9	0.32 0.22	6.7 6.3	3.7 3.3	4.6	2.3	7.3 6.7	1.1 0.7	0.95 0.85	0.2	0.1	0.1

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT223			SC-73			~~04-11-10~~ 06-03-16

Fig 18. Package outline SOT223 (SC-73)

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

8. Revision history

Table 7. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
ACT108W-600E v.5	20100713	Product data sheet	-	ACT108W-600E v.4
Modifications:	• Various changes to content.			
ACT108W-600E v.4	20091209	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

9. Legal information

9.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

9.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

9.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on a weakness or default in the customer application/use or the application/use of customer's third party customer(s) (hereinafter both referred to as "Application"). It is customer's sole responsibility to check whether the NXP Semiconductors product is suitable and fit for the Application planned. Customer has to do all necessary testing for the Application in order to avoid a default of the Application and the product. NXP Semiconductors does not accept any liability in this respect.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding. Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

Non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Adelante, **Bitport**, **Bitsound**, **CoolFlux**, **CoReUse**, **DESFire**, **EZ-HV**, **FabKey**, **GreenChip**, **HiPerSmart**, **HITAG**, **I²C-bus** logo, **ICODE**, **I-CODE**, **ITEC**, **Labelution**, **MIFARE**, **MIFARE Plus**, **MIFARE Ultralight**, **MoReUse**, **QLPAK**, **Silicon Tuner**, **SiliconMAX**, **SmartXA**, **STARplug**, **TOPFET**, **TrenchMOS**, **TriMedia** and **UCODE** — are trademarks of NXP B.V.

HD Radio and **HD Radio** logo — are trademarks of iBiquity Digital Corporation.

10. Contact information

For more information, please visit: http://www.nxp.com

For sales office addresses, please send an email to: salesaddresses@nxp.com

All information provided in this document is subject to legal disclaimers.

© NXP B.V. 2010. All rights reserved.

11. Contents

1 Product profile 1
1.1 General description 1
1.2 Features and benefits 1
1.3 Applications 1
1.4 Quick reference data 1
2 Pinning information 2
3 Ordering information 2
4 Limiting values 3
5 Thermal characteristics 6
6 Characteristics 7
7 Package outline 10
8 Revision history 11
9 Legal information 12
9.1 Data sheet status 12
9.2 Definitions 12
9.3 Disclaimers 12
9.4 Trademarks 13
10 Contact information 13

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2010. **All rights reserved.**

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 13 July 2010
Document identifier: ACT108W-600E