
JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

TO-126 Plastic-Encapsulate Transistors

MJE13003 TRANSISTOR (NPN)

TO-126



1 . BASE

2. COLLECTOR

3. EMITTER

FEATURES

- Power Switching Applications

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	600	V
V_{CEO}	Collector-Emitter Voltage	400	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current -Continuous	1	A
P_C	Collector Power Dissipation	1.25	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	100	℃/W
T_j	Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~+150	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C= 0.1mA,I_E=0	600			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C= 1mA,I_B=0	400			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=0.1mA,I_C=0	6			V
Collector cut-off current	I_{CBO}	V_{CB}=600V,I_E=0			100	uA
Collector cut-off current	I_{CEO}	V_{CE}=400V,I_B=0			100	uA
Emitter cut-off current	I_{EBO}	V_{EB}=7V,I_C=0			10	uA
DC current gain	$h_{FE(1)}$*	V_{CE}=10V, I_C=200mA	9		40	
	$h_{FE(2)}$	V_{CE}=10V, I_C=250μA	5			
Collector-emitter saturation voltage	$V_{CE(sat)1}$	I_C=200mA,I_B=40mA			0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=200mA,I_B=40mA			1.1	V
Transition frequency	f_T	V_{CE}=10V, I_C=100mA,f=1MHz	5			MHz
Fall time	t_f	I_C=100mA			0.5	μs
Storage time	t_S*	I_C=100mA	2		4	


CLASSIFICATION of $h_{FE(1)}$

Range	9-15	15-20	20-25	25-30	30-35	35-40

CLASSIFICATION of t_S

Rank	A1	A2	B1	B2
Range	2-2.5	2.5-3	3-3.5	3.5-4

TO-126 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	2.500	2.900	0.098	0.114
A1	1.100	1.500	0.043	0.059
b	0.660	0.860	0.026	0.034
b1	1.170	1.370	0.046	0.054
c	0.450	0.600	0.018	0.024
D	7.400	7.800	0.291	0.307
E	10.600	11.000	0.417	0.433
e	2.290 TYP		0.090 TYP	
e1	4.480	4.680	0.176	0.184
h	0.000	0.300	0.000	0.012
L	15.300	15.700	0.602	0.618
L1	2.100	2.300	0.083	0.091
P	3.900	4.100	0.154	0.161
Φ	3.000	3.200	0.118	0.126