
International
IOR Rectifier

# IRFZ48NPbF

HEXFET® Power MOSFET

- Advanced Process Technology
- Ultra Low On-Resistance
- Dynamic dv/dt Rating
- 175°C Operating Temperature
- Fast Switching
- Fully Avalanche Rated
- Lead-Free




$V_{DSS}$ = 55V

$R_{DS(on)}$ = 14mΩ

$I_D$ = 64A

## Description

Advanced HEXFET® Power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The TO-220 package is universally preferred for all commercial-industrial applications at power dissipation levels to approximately 50 watts. The low thermal resistance and low package cost of the TO-220 contribute to its wide acceptance throughout the industry.



TO-220AB

## Absolute Maximum Ratings


| | Parameter | Max. | Units |
|---|---|---|---|
| $I_D$ @ $T_C$ = 25°C | Continuous Drain Current, $V_{GS}$ @ 10V | 64 | A |
| $I_D$ @ $T_C$ = 100°C | Continuous Drain Current, $V_{GS}$ @ 10V | 45 | |
| $I_{DM}$ | Pulsed Drain Current ① | 210 | |
| $P_D$ @$T_C$ = 25°C | Power Dissipation | 130 | W |
| | Linear Derating Factor | 0.83 | W/°C |
| $V_{GS}$ | Gate-to-Source Voltage | ± 20 | V |
| $I_{AR}$ | Avalanche Current① | 32 | A |
| $E_{AR}$ | Repetitive Avalanche Energy① | 13 | mJ |
| dv/dt | Peak Diode Recovery dv/dt ③ | 5.0 | V/ns |
| $T_J$<br>$T_{STG}$ | Operating Junction and<br>Storage Temperature Range | -55 to + 175 | °C |
| | Soldering Temperature, for 10 seconds | 300 (1.6mm from case ) | |
| | Mounting torque, 6-32 or M3 srew | 10 lbf•in (1.1N•m) | |

## Thermal Resistance

| | Parameter | Typ. | Max. | Units |
|---|---|---|---|---|
| $R_{\theta JC}$ | Junction-to-Case | —— | 1.15 | °C/W |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface | 0.50 | —— | |
| $R_{\theta JA}$ | Junction-to-Ambient | —— | 62 | |


## Electrical Characteristics @ $T_J$ = 25°C (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|---|---|---|---|---|---|---|
| $V_{(BR)DSS}$ | Drain-to-Source Breakdown Voltage | 55 | — | — | V | $V_{GS}$ = 0V, $I_D$ = 250µA |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient | — | 0.058 | — | V/°C | Reference to 25°C, $I_D$ = 1mA |
| $R_{DS(on)}$ | Static Drain-to-Source On-Resistance | — | — | 14 | mΩ | $V_{GS}$ = 10V, $I_D$ = 32A ④ |
| $V_{GS(th)}$ | Gate Threshold Voltage | 2.0 | — | 4.0 | V | $V_{DS}$ = $V_{GS}$, $I_D$ = 250µA |
| $g_{fs}$ | Forward Transconductance | 24 | — | — | S | $V_{DS}$ = 25V, $I_D$ = 32A④ |
| $I_{DSS}$ | Drain-to-Source Leakage Current | — | — | 25 | µA | $V_{DS}$ = 55V, $V_{GS}$ = 0V |
| | | — | — | 250 | | $V_{DS}$ = 44V, $V_{GS}$ = 0V, $T_J$ = 150°C |
| $I_{GSS}$ | Gate-to-Source Forward Leakage | — | — | 100 | nA | $V_{GS}$ = 20V |
| | Gate-to-Source Reverse Leakage | — | — | -100 | | $V_{GS}$ = -20V |
| $Q_g$ | Total Gate Charge | — | — | 81 | nC | $I_D$ = 32A |
| $Q_{gs}$ | Gate-to-Source Charge | — | — | 19 | | $V_{DS}$ = 44V |
| $Q_{gd}$ | Gate-to-Drain ("Miller") Charge | — | — | 30 | | $V_{GS}$ = 10V, See Fig. 6 and 13 |
| $t_{d(on)}$ | Turn-On Delay Time | — | 12 | — | ns | $V_{DD}$ = 28V |
| $t_r$ | Rise Time | — | 78 | — | | $I_D$ = 32A |
| $t_{d(off)}$ | Turn-Off Delay Time | — | 34 | — | | $R_G$ = 0.85Ω |
| $t_f$ | Fall Time | — | 50 | — | | $V_{GS}$ = 10V, See Fig. 10 ④ |
| $L_D$ | Internal Drain Inductance | — | 4.5 | — | nH | Between lead, 6mm (0.25in.) from package and center of die contact |
| $L_S$ | Internal Source Inductance | — | 7.5 | — | | |
| $C_{iss}$ | Input Capacitance | — | 1970 | — | pF | $V_{GS}$ = 0V |
| $C_{oss}$ | Output Capacitance | — | 470 | — | | $V_{DS}$ = 25V |
| $C_{rss}$ | Reverse Transfer Capacitance | — | 120 | — | | $f$ = 1.0MHz, See Fig. 5 |
| $E_{AS}$ | Single Pulse Avalanche Energy② | — | 700⑤ | 190⑥ | mJ | $I_{AS}$ = 32A, L = 0.37mH |




## Source-Drain Ratings and Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|---|---|---|---|---|---|---|
| $I_S$ | Continuous Source Current (Body Diode) | — | — | 64 | A | MOSFET symbol showing the integral reverse p-n junction diode. |
| $I_{SM}$ | Pulsed Source Current (Body Diode)① | — | — | 210 | | |
| $V_{SD}$ | Diode Forward Voltage | — | — | 1.3 | V | $T_J$ = 25°C, $I_S$ = 32A, $V_{GS}$ = 0V ④ |
| $t_{rr}$ | Reverse Recovery Time | — | 68 | 100 | ns | $T_J$ = 25°C, $I_F$ = 32A |
| $Q_{rr}$ | Reverse Recovery Charge | — | 220 | 330 | nC | di/dt = 100A/µs ④ |
| $t_{on}$ | Forward Turn-On Time | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S$+$L_D$) | | | | |




**Notes:**

① Repetitive rating; pulse width limited by max. junction temperature. ( See fig. 11 )

② Starting $T_J$ = 25°C, L = 0.37mH $R_G$ = 25Ω, $I_{AS}$ = 32A. (See Figure 12)

③ $I_{SD}$ ≤ 32A, di/dt ≤ 220A/µs, $V_{DD}$ ≤ $V_{(BR)DSS}$, $T_J$ ≤ 175°C

④ Pulse width ≤ 400µs; duty cycle ≤ 2%.

⑤ This is the destructive value not limited to the thermal limit.

⑥ This is the thermal limited value.





**Fig 1.** Typical Output Characteristics





**Fig 2.** Typical Output Characteristics





**Fig 3.** Typical Transfer Characteristics





**Fig 4.** Normalized On-Resistance Vs. Temperature





**Fig 5.** Typical Capacitance Vs. Drain-to-Source Voltage





**Fig 6.** Typical Gate Charge Vs. Gate-to-Source Voltage





**Fig 7.** Typical Source-Drain Diode Forward Voltage





**Fig 8.** Maximum Safe Operating Area





**Fig 9.** Maximum Drain Current Vs. Case Temperature





**Fig 10a.** Switching Time Test Circuit





**Fig 10b.** Switching Time Waveforms





**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Case





**Fig 12a.** Unclamped Inductive Test Circuit





**Fig 12b.** Unclamped Inductive Waveforms





**Fig 12c.** Maximum Avalanche Energy Vs. Drain Current





**Fig 13a.** Basic Gate Charge Waveform







**Fig 13b.** Gate Charge Test Circuit

## Peak Diode Recovery dv/dt Test Circuit





* Reverse Polarity of D.U.T for P-Channel




*** $V_{GS}$ = 5.0V for Logic Level and 3V Drive Devices

**Fig 14.** For N-channel HEXFET® power MOSFETs

## TO-220AB Package Outline (Dimensions are shown in millimeters (inches))




NOTES:

1.– DIMENSIONING AND TOLERANCING AS PER ASME Y14.5 M– 1994.
2.– DIMENSIONS ARE SHOWN IN INCHES [MILLIMETERS].
3.– LEAD DIMENSION AND FINISH UNCONTROLLED IN L1.
4.– DIMENSION D, D1 & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5.– DIMENSION b1, b3 & c1 APPLY TO BASE METAL ONLY.
6.– CONTROLLING DIMENSION : INCHES.
7.– THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS E,H1,D2 & E1
8.– DIMENSION E2 X H1 DEFINE A ZONE WHERE STAMPING AND SINGULATION IRREGULARITIES ARE ALLOWED.
9.– OUTLINE CONFORMS TO JEDEC TO-220, EXCEPT A2 (max.) AND D2 (min.) WHERE DIMENSIONS ARE DERIVED FROM THE ACTUAL PACKAGE OUTLINE.

| SYMBOL | DIMENSIONS | | | | NOTES |
|---|---|---|---|---|---|
| | MILLIMETERS | | INCHES | | |
| | MIN. | MAX. | MIN. | MAX. | |
| A | 3.56 | 4.83 | .140 | .190 | |
| A1 | 0.51 | 1.40 | .020 | .055 | |
| A2 | 2.03 | 2.92 | .080 | .115 | |
| b | 0.38 | 1.01 | .015 | .040 | |
| b1 | 0.38 | 0.97 | .015 | .038 | 5 |
| b2 | 1.14 | 1.78 | .045 | .070 | |
| b3 | 1.14 | 1.73 | .045 | .068 | 5 |
| c | 0.36 | 0.61 | .014 | .024 | |
| c1 | 0.36 | 0.56 | .014 | .022 | 5 |
| D | 14.22 | 16.51 | .560 | .650 | 4 |
| D1 | 8.38 | 9.02 | .330 | .355 | |
| D2 | 11.68 | 12.88 | .460 | .507 | 7 |
| E | 9.65 | 10.67 | .380 | .420 | 4,7 |
| E1 | 6.86 | 8.89 | .270 | .350 | 7 |
| E2 | – | 0.76 | – | .030 | 8 |
| e | 2.54 BSC | | .100 BSC | | |
| e1 | 5.08 BSC | | .200 BSC | | |
| H1 | 5.84 | 6.86 | .230 | .270 | 7,8 |
| L | 12.70 | 14.73 | .500 | .580 | |
| L1 | – | 6.35 | – | .250 | 3 |
| øP | 3.54 | 4.08 | .139 | .161 | |
| Q | 2.54 | 3.42 | .100 | .135 | |

LEAD ASSIGNMENTS

HEXFET
1.- GATE
2.- DRAIN
3.- SOURCE


IGBTs, CoPACK
1.- GATE
2.- COLLECTOR
3.- EMITTER

DIODES
1.- ANODE/OPEN
2.- CATHODE
3.- ANODE

## TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010
LOT CODE 1789
ASSEMBLED ON WW 19, 2000
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead - Free"




**Notes:**

**1. For an Automotive Qualified version of this part please see http://www.irf.com/product-info/auto/**

**2. For the most current drawing please refer to IR website at http://www.irf.com/package/**

Data and specifications subject to change without notice.
This product has been designed and qualified for the Industrial market.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.09/2010

## IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie") .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (**www.infineon.com**).

## WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.