
Cool MOS™ Power Transistor

V_{DS}	650	V
$R_{DS(on)}$	0.19	Ω
I_D	20.7	A


Feature

- New revolutionary high voltage technology
- Worldwide best $R_{DS(on)}$ in TO 220
- Ultra low gate charge
- Periodic avalanche rated
- Extreme d*v*/d*t* rated
- High peak current capability
- Improved transconductance
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC[0)] for target applications

PG-TO262 PG-TO220FP PG-TO220



Type	Package	Ordering Code	Marking
SPP20N65C3	PG-TO220	Q67040-S4556	20N65C3
SPA20N65C3	PG-TO220FP	SP000216362	20N65C3
SPI20N65C3	PG-TO262	Q67040-S4560	20N65C3



Maximum Ratings

Parameter	Symbol	Value		Unit
		SPP_I	SPA	
Continuous drain current	I_D			A
T_C = 25 °C		20.7	20.7[1)]	
T_C = 100 °C		13.1	13.1[1)]	
Pulsed drain current, t_p limited by T_{jmax}	$I_{D\ puls}$	62.1	62.1	A
Avalanche energy, single pulse	E_{AS}	690	690	mJ
I_D=3.5A, V_{DD}=50V				
Avalanche energy, repetitive t_{AR} limited by T_{jmax}[2)]	E_{AR}	1	1	
I_D=7A, V_{DD}=50V				
Avalanche current, repetitive t_{AR} limited by T_{jmax}	I_{AR}	7	7	A
Gate source voltage	V_{GS}	±20	±20	V
Gate source voltage AC (f >1Hz)	V_{GS}	±30	±30	
Power dissipation, T_C = 25°C	P_{tot}	208	34.5	W
Operating and storage temperature	T_j , T_{stg}	-55...+150		°C

Maximum Ratings

Parameter	Symbol	Value	Unit
Drain Source voltage slope V_{DS} = 480 V, I_D = 20.7 A, T_j = 125 °C	d*v*/d*t*	50	V/ns

Thermal Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Thermal resistance, junction - case	R_{thJC}	-	-	0.6	K/W
Thermal resistance, junction - case, FullPAK	R_{thJC_FP}	-	-	3.6	
Thermal resistance, junction - ambient, leaded	R_{thJA}	-	-	62	
Thermal resistance, junction - ambient, FullPAK	R_{thJA_FP}	-	-	80	
SMD version, device on PCB: @ min. footprint @ 6 cm^2 cooling area [3)]	R_{thJA}	 - -	 - 35	 62 -	
Soldering temperature, wavesoldering 1.6 mm (0.063 in.) from case for 10s	T_{sold}	-	-	260	°C

Electrical Characteristics, at T_j=25°C unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0V, I_D=0.25mA	650	-	-	V
Drain-Source avalanche breakdown voltage	$V_{(BR)DS}$	V_{GS}=0V, I_D=7A	-	730	-	
Gate threshold voltage	$V_{GS(th)}$	I_D=1000µA, V_{GS}=V_{DS}	2.1	3	3.9	
Zero gate voltage drain current	I_{DSS}	V_{DS}=600V, V_{GS}=0V, T_j=25°C T_j=150°C	 - -	 0.1 -	 1 100	µA
Gate-source leakage current	I_{GSS}	V_{GS}=20V, V_{DS}=0V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=13.1A T_j=25°C T_j=150°C	 - -	 0.16 0.43	 0.19 -	Ω
Gate input resistance	R_G	*f*=1MHz, open drain	-	0.54	-	

Electrical Characteristics

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Transconductance	g_{fs}	$V_{DS}\geq 2*I_D*R_{DS(on)max}$, I_D=13.1A	-	17.5	-	S
Input capacitance	C_{iss}	V_{GS}=0V, V_{DS}=25V, f=1MHz	-	2400	-	pF
Output capacitance	C_{oss}		-	780	-	
Reverse transfer capacitance	C_{rss}		-	50	-	
Effective output capacitance,[4] energy related	$C_{o(er)}$	V_{GS}=0V, V_{DS}=0V to 480V	-	83	-	
Effective output capacitance,[5] time related	$C_{o(tr)}$		-	160	-	
Turn-on delay time	$t_{d(on)}$	V_{DD}=380V, V_{GS}=0/13V, I_D=20.7A, R_G=3.6Ω, T_j=125	-	10	-	ns
Rise time	t_r	V_{DD}=380V, V_{GS}=0/13V, I_D=20.7A, R_G=3.6Ω	-	5	-	
Turn-off delay time	$t_{d(off)}$		-	67	100	
Fall time	t_f		-	4.5	12	

Gate Charge Characteristics

Gate to source charge	Q_{gs}	V_{DD}=480V, I_D=20.7A	-	11	-	nC
Gate to drain charge	Q_{gd}		-	33	-	
Gate charge total	Q_g	V_{DD}=480V, I_D=20.7A, V_{GS}=0 to 10V	-	87	114	
Gate plateau voltage	$V_{(plateau)}$	V_{DD}=480V, I_D=20.7A	-	5.5	-	V

[0]J-STD20 and JESD22

[1]Limited only by maximum temperature

[2]Repetitve avalanche causes additional power losses that can be calculated as $P_{AV}=E_{AR}*f$.

[3]Device on 40mm*40mm*1.5mm epoxy PCB FR4 with 6cm² (one layer, 70 µm thick) copper area for drain connection. PCB is vertical without blown air.

[4]$C_{o(er)}$ is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% V_{DSS}.


[5]$C_{o(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% V_{DSS}.

Electrical Characteristics

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Inverse diode continuous forward current	I_S	T_C=25°C	-	-	20.7	A
Inverse diode direct current, pulsed	I_{SM}		-	-	62.1	
Inverse diode forward voltage	V_{SD}	V_{GS}=0V, I_F=I_S	-	1	1.2	V
Reverse recovery time	t_{rr}	V_R=480V, I_F=I_S , di_F/dt=100A/µs	-	500	800	ns
Reverse recovery charge	Q_{rr}		-	11	-	µC
Peak reverse recovery current	I_{rrm}		-	70	-	A
Peak rate of fall of reverse recovery current	di_{rr}/dt	T_j=25°C	-	1400	-	A/µs


Typical Transient Thermal Characteristics

Symbol	Value		Unit	Symbol	Value		Unit
	SPP_I	SPA			SPP_I	SPA	
R_{th1}	0.00769	0.00769	K/W	C_{th1}	0.0003763	0.0003763	Ws/K
R_{th2}	0.015	0.015		C_{th2}	0.001411	0.001411	
R_{th3}	0.029	0.029		C_{th3}	0.001931	0.001931	
R_{th4}	0.114	0.163		C_{th4}	0.005297	0.005297	
R_{th5}	0.136	0.323		C_{th5}	0.012	0.008453	
R_{th6}	0.059	2.526		C_{th6}	0.091	0.412	




1 Power dissipation

$P_{tot} = f(T_C)$



2 Power dissipation FullPAK


$P_{tot} = f(T_C)$



3 Safe operating area

$I_D = f(V_{DS})$


parameter : $D = 0$, T_C=25°C



4 Safe operating area FullPAK

$I_D = f(V_{DS})$


parameter: $D = 0$, $T_C = 25°C$



5 Transient thermal impedance FullPAK

$Z_{thJC} = f(t_p)$


parameter: $D = t_p/t$



6 Typ. output characteristic

$I_D = f(V_{DS})$; T_j=25°C


parameter: t_p = 10 µs, V_{GS}



7 Typ. output characteristic

$I_D = f(V_{DS})$; T_j=150°C


parameter: t_p = 10 µs, V_{GS}



8 Typ. drain-source on resistance

$R_{DS(on)} = f(I_D)$


parameter: T_j=150°C, V_{GS}



9 Drain-source on-state resistance

$R_{DS(on)} = f(T_j)$


parameter : I_D = 13.1 A, V_{GS} = 10 V



10 Typ. transfer characteristics

$I_D = f(V_{GS})$; $V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$


parameter: t_p = 10 µs



11 Typ. gate charge

$V_{GS} = f(Q_{Gate})$


parameter: I_D = 20.7 A pulsed



12 Forward characteristics of body diode

$I_F = f(V_{SD})$


parameter: T_j , tp = 10 µs



13 Typ. switching time

$t = f(I_D)$, inductive load, T_j=125°C


par.: V_{DS}=380V, V_{GS}=0/+13V, R_G=3.6Ω



14 Typ. switching time

$t = f(R_G)$, inductive load, T_j=125°C


par.: V_{DS}=380V, V_{GS}=0/+13V, I_D=20.7 A



15 Typ. drain current slope

di/dt = f(R_G), inductive load, T_j = 125°C


par.: V_{DS}=380V, V_{GS}=0/+13V, I_D=20.7A



16 Typ. drain source voltage slope

dv/dt = f(R_G), inductive load, T_j = 125°C


par.: V_{DS}=380V, V_{GS}=0/+13V, I_D=20.7A



17 Typ. switching losses

$E = f(I_D)$, inductive load, T_j=125°C


par.: V_{DS}=380V, V_{GS}=0/+13V, R_G=3.6Ω



18 Typ. switching losses

$E = f(R_G)$, inductive load, T_j=125°C


par.: V_{DS}=380V, V_{GS}=0/+13V,I_D=11A



19 Avalanche SOA

$I_{AR} = f(t_{AR})$


par.: $T_j \leq 150$ °C



20 Avalanche energy


$E_{AS} = f(T_j)$

par.: I_D = 3.5 A, V_{DD} = 50 V



21 Drain-source breakdown voltage


$V_{(BR)DSS} = f(T_j)$



22 Avalanche power losses

$P_{AR} = f(f)$


parameter: E_{AR}=1mJ



23 Typ. capacitances


$C = f(V_{DS})$

parameter: V_{GS}=0V, f=1 MHz




24 Typ. C_{oss} stored energy


$E_{oss}=f(V_{DS})$



Definition of diodes switching characteristics




PG-TO220-3-1, PG-TO220-3-21



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.57	0.169	0.180
A1	1.17	1.40	0.046	0.055
A2	2.15	2.72	0.085	0.107
b	0.65	0.86	0.026	0.034
b1	0.95	1.40	0.037	0.055
b2	0.95	1.15	0.037	0.045
b3	0.65	1.15	0.026	0.045
c	0.33	0.60	0.013	0.024
D	14.81	15.95	0.583	0.628
D1	8.51	9.45	0.335	0.372
D2	12.19	13.10	0.480	0.516
E	9.70	10.36	0.382	0.408
E1	6.50	8.60	0.256	0.339
e	2.54		0.100	
e1	5.08		0.200	
N	3		3	
H1	5.90	6.90	0.232	0.272
L	13.00	14.00	0.512	0.551
L1	-	4.80	-	0.189
øP	3.60	3.89	0.142	0.153
Q	2.60	3.00	0.102	0.118

DOCUMENT NO.	Z8B00003318
SCALE	0 2.5 0 2.5 5mm
EUROPEAN PROJECTION	
ISSUE DATE	23-08-2007
REVISION	05


PG-TO220-3-31/3-111 Fully isolated package (2500 VAC; 1 minute)



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.55	4.85	0.179	0.191
A1	2.55	2.85	0.100	0.112
A2	2.42	2.72	0.095	0.107
b	0.65	0.85	0.026	0.033
b1	0.95	1.33	0.037	0.052
b2	0.95	1.51	0.037	0.059
b3	0.65	1.33	0.026	0.052
b4	0.65	1.51	0.026	0.059
c	0.40	0.63	0.016	0.025
D	15.85	16.15	0.624	0.636
D1	9.53	9.83	0.375	0.387
E	10.35	10.65	0.407	0.419
e	2.54		0.100	
e1	5.08		0.200	
N	3		3	
H	29.45	29.75	1.159	1.171
L	13.45	13.75	0.530	0.541
L1	3.15	3.45	0.124	0.136
øP	2.95	3.20	0.116	0.126
Q	3.15	3.50	0.124	0.138

REFERENCE
../..
SCALE 0 2.5 0 2.5 5mm
EUROPEAN PROJECTION
ISSUE DATE 08-01-2007
FILE TO220_2

PG-TO262-3-1, PG-TO262-3-21 (I²-PAK)



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.300	4.572	0.169	0.180
A1	2.150	2.718	0.085	0.107
b	0.650	0.864	0.026	0.034
b1	0.635	1.400	0.025	0.055
c	0.330	0.600	0.013	0.024
c1	1.170	1.400	0.046	0.055
D	8.509	9.450	0.335	0.372
D1	6.900	-	0.272	-
E	9.700	10.363	0.382	0.408
E1	6.500	8.600	0.256	0.339
e	2.540		0.100	
e1	5.080		0.200	
N	3		3	
L	13.000	14.000	0.512	0.551
L1	-	4.800	-	0.189
L2	-	1.727	-	0.068

REFERENCE
JEDEC TO262

0
2.5
0 2.5
5mm

EUROPEAN PROJECTION

ISSUE DATE
05-05-2006

FILE
TO262_1

Published by
Infineon Technologies AG,
Bereichs Kommunikation
St.-Martin-Strasse 53,
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!
The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Reprensatives worldwide (see address list).

Warnings
Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.