48 MHZ USB CLOCK SOURCE

ICS5OSK482

Description


The ICS5OSK482 is a low cost integrated clock synthesizer solution designed for replacing crystals and crystal oscillators.

The ICS5OSK482 generates a very accurate 48.00 MHz clock output.


Features

- 14.31818 MHz crystal input
- The 48.00 MHz CLK output is USB2.0 reference clock compliant
- Output duty cycle 45/55% (worst case)
- Advanced, low-power CMOS process
- Industrial temperature range (-40 to +85°C)
- Packaged in 5-pin TSOT
- 3.3 V supply voltage
- Pb (lead) free package available
- Short term C-C Jitter of 100 ps

Block Diagram



Pin Assignment



Pin Descriptions

Pin Number	Pin Name	Pin Type	Pin Description
1	X1	Input	14.31818 MHz crystal input. Connect to a parallel resonant fundamental crystal.
2	GND	Power	Connect to ground.
3	CLK	Output	PLL output clock. Internal pull-down resistor.
4	VDD	Power	Connect to 3.3 V.
5	X2	Output	14.31818 MHz crystal output.

External Components

External Crystal

The ICS5OSK482 requires a 14.31818 MHz crystal. In order to minimize ppm errors, the PCB should include pads for crystal capacitors from pins X1 to ground and X2 to ground to optimize the initial accuracy. The capacitor value can be determined by tuning the PCB so that the error on the reference output is equal to the initial crystal error.

Crystal Load Capacitors

The device crystal connections should include pads for small capacitors from pins X1 to ground and X2 to ground. These capacitors are used to adjust the stray capacitance of the board to match the nominally required crystal load capacitance. Because load capacitance can only be increased in this trimming process, it is important to keep stray capacitance to a minimum by using very short PCB traces (and no vias) between the crystal and device. Crystal capacitors must be connected from each of the pins X1 and X2 to ground.

The value (in pF) of these crystal caps should equal (C_L -6 pF) * 2. In the equation, C_L = crystal load capacitance in pF. Example: For a crystal with a 8 pF load capacitance, each crystal capacitor would be 4 pF [(8-6) x 2 = 4].

Absolute Maximum Ratings

Stresses above the ratings listed below can cause permanent damage to the ICS5OSK482. These ratings, which are standard values for ICS commercially rated parts, are stress ratings only. Functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods can affect product reliability. Electrical parameters are guaranteed only over the recommended operating temperature range.

Item	Rating
Max Supply Voltage, VDD	7 V
Logic Inputs	-0.5 V to VDD+0.5 V
Ambient Operating Temperature	-40 to +85°C
Storage Temperature	-65 to +150°C
Junction Temperature	125°C
Soldering Temperature	260°C

Recommended Operation Conditions

Parameter	Min.	Typ.	Max.	Units
Ambient Operating Temperature	-40		+85	°C
Power Supply Voltage (measured in respect to GND)	+3.135	+3.3	+3.465	V

DC Electrical Characteristics

VDD=3.3 V ±5%, Ambient temperature -40 to +85°C, CL = 15 pF, unless stated otherwise

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Operating Voltage	VDD		3.135		3.465	V
Output High Voltage	V_{OH}	I_{OH} = -12 mA	2.4			V
Output Low Voltage	V_{OL}	I_{OL} = 12 mA			0.4	V
IDD Operating Supply Current	IDD	No Load		TBD		mA
Short Circuit Current	I_{OS}	CLK output		±70		mA
Input Capacitance	C_{IN}			4		pF
Nominal Output Impedance				20		Ω

AC Electrical Characteristics


VDD = 3.3 V ±5%, Ambient Temperature -40 to +85°C, CL = 15 pF, unless stated otherwise

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Input Frequency, crystal input	f_{IN}			14.31818		MHz
Output Frequency	f_{OUT}			48		MHz
Output Clock Rise Time	t_{OR}	0.8 to 2.0 V, Note 1		1		ns
Output Clock Fall Time	t_{OF}	2.0 to 0.8 V, Note 1		1		ns
Output Clock Duty Cycle	t_{DC}	1.5 V	45	50	60	%
Absolute Clock Period Jitter	t_{JA}	Deviation from mean, Note 1		100		ps

Note 1: Measured with a 15 pF load.

Package Outline and Package Dimensions (5-pin TSOT)

Package dimensions are kept current with JEDEC Publication No. 95



	Millimeters	
Symbol	Min	Max
A	—	1.00
A1	0.01	0.10
A2	0.84	0.90
b	0.30	0.45
c	0.12	0.20
D	2.90 BASIC	
E	2.80 BASIC	
E1	1.60 BASIC	
e	0.95 BASIC	
e1	1.90 BASIC	
L	0.30	0.50
L1	0.60 REF	
L2	0.25 BASIC	
θ	0°	8°
aaa	—	0.10

Ordering Information

Part / Order Number	Marking	Shipping Packaging	Package	Temperature
ICS5OSK482TILF	2TIL	Tubes	5-pin TSOT	-40 to +85° C
ICS5OSK482TILFT	2TIL	Tape and Reel	5-pin TSOT	-40 to +85° C

Parts that are ordered with a "LF" suffix to the part number are the Pb-Free configuration and are RoHS compliant.

While the information presented herein has been checked for both accuracy and reliability, Integrated Circuit Systems (ICS) assumes no responsibility for either its use or for the infringement of any patents or other rights of third parties, which would result from its use. No other circuits, patents, or licenses are implied. This product is intended for use in normal commercial applications. Any other applications such as those requiring extended temperature range, high reliability, or other extraordinary environmental requirements are not recommended without additional processing by ICS. ICS reserves the right to change any circuitry or specifications without notice. ICS does not authorize or warrant any ICS product for use in life support devices or critical medical instruments.

Innovate with IDT and accelerate your future networks. Contact:

www.IDT.com

For Sales
800-345-7015
408-284-8200
Fax: 408-284-2775

For Tech Support
<product line email>
<product line phone>

Corporate Headquarters
Integrated Device Technology, Inc.
6024 Silver Creek Valley Road
San Jose, CA 95138
United States
800 345 7015
+408 284 8200 (outside U.S.)

Asia Pacific and Japan
Integrated Device Technology
Singapore (1997) Pte. Ltd.
Reg. No. 199707558G
435 Orchard Road
#20-03 Wisma Atria
Singapore 238877
+65 6 887 5505

Europe
IDT Europe, Limited
321 Kingston Road
Leatherhead, Surrey
KT22 7TU
England
+44 1372 363 339

www.IDT.com

© 2006 Integrated Device Technology, Inc. All rights reserved. Product specifications subject to change without notice. IDT and the IDT logo are trademarks of Integrated Device Technology, Inc. Accelerated Thinking is a service mark of Integrated Device Technology, Inc. All other brands, product names and marks are or may be trademarks or registered trademarks used to identify products or services of their respective owners.
Printed in USA