



## Silicon Schottky Diode


- General-purpose diode for high-speed switching
- Circuit protection
- Voltage clamping
- High-level detecting and mixing
- Pb-free (RoHS compliant) package
- Qualified according AEC Q101<sup>1)</sup>




### **BAS140W** **BAS40-02L**




### **BAS40**




### **BAS40-04**




### **BAS40-05** **BAS40-05W**



### **BAS40-06** **BAS40-06W**



### **BAS40-07** **BAS40-07W**



**ESD (Electrostatic discharge) sensitive device, observe handling precaution!**

| Type        | Package  | Configuration    | Marking |
|-------------|----------|------------------|---------|
| BAS140W     | SOD323   | single           | white 4 |
| BAS40       | SOT23    | single           | 43s     |
| BAS40-02L * | TSLP-2-1 | single, leadless | FF      |
| BAS40-04    | SOT23    | series           | 44s     |
| BAS40-05    | SOT23    | common cathode   | 45s     |
| BAS40-05W   | SOT323   | common cathode   | 45s     |
| BAS40-06    | SOT23    | common anode     | 46s     |
| BAS40-06W   | SOT323   | common anode     | 46s     |
| BAS40-07    | SOT143   | parallel pair    | 47s     |
| BAS40-07W   | SOT343   | parallel pair    | 47s     |

<sup>1)</sup> BAS40-02L is not qualified according AEC Q101

**Maximum Ratings** at  $T_A = 25\text{ °C}$ , unless otherwise specified

| Parameter                                                                                                                                                                                                                                                                                                                                       | Symbol    | Value                                                | Unit |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------|------|
| Diode reverse voltage                                                                                                                                                                                                                                                                                                                           | $V_R$     | 40                                                   | V    |
| Forward current                                                                                                                                                                                                                                                                                                                                 | $I_F$     | 120                                                  | mA   |
| Non-repetitive peak surge forward current<br>$t \leq 10\text{ms}$                                                                                                                                                                                                                                                                               | $I_{FSM}$ | 200                                                  |      |
| Total power dissipation<br>BAS140W, $T_S \leq 113\text{°C}$<br>BAS40, BAS40-07, $T_S \leq 81\text{°C}$<br>BAS40-02L, $T_S \leq 127\text{°C}$<br>BAS40-04, BAS40-06, $T_S \leq 56\text{°C}$<br>BAS40-06W, $T_S \leq 106\text{°C}$<br>BAS40-05, $T_S \leq 31\text{°C}$<br>BAS40-05W, $T_S \leq 98\text{°C}$<br>BAS40-07W, $T_S \leq 118\text{°C}$ | $P_{tot}$ | 250<br>250<br>250<br>250<br>250<br>250<br>250<br>250 | mW   |
| Junction temperature                                                                                                                                                                                                                                                                                                                            | $T_j$     | 150                                                  | °C   |
| Operating temperature range                                                                                                                                                                                                                                                                                                                     | $T_{op}$  | -55 ... 150                                          |      |
| Storage temperature                                                                                                                                                                                                                                                                                                                             | $T_{stg}$ | -55 ... 150                                          |      |

#### Thermal Resistance

| Parameter                                                                                                                                                    | Symbol     | Value                                                                                                       | Unit |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------------------------------|------|
| Junction - soldering point <sup>1)</sup><br>BAS140W<br>BAS40, BAS40-07<br>BAS40-02L<br>BAS40-04, BAS40-06<br>BAS40-06W<br>BAS40-05<br>BAS40-05W<br>BAS40-07W | $R_{thJS}$ | $\leq 150$<br>$\leq 275$<br>$\leq 90$<br>$\leq 375$<br>$\leq 175$<br>$\leq 475$<br>$\leq 205$<br>$\leq 125$ | K/W  |

<sup>1)</sup>For calculation of  $R_{thJA}$  please refer to Application Note AN077 (Thermal Resistance Calculation)


**Electrical Characteristics** at  $T_A = 25^\circ\text{C}$ , unless otherwise specified

| Parameter                                                                                 | Symbol       | Values            |                   |                    | Unit          |
|-------------------------------------------------------------------------------------------|--------------|-------------------|-------------------|--------------------|---------------|
|                                                                                           |              | min.              | typ.              | max.               |               |
| DC Characteristics                                                                        |              |                   |                   |                    |               |
| Breakdown voltage<br>$I_{(BR)} = 10\ \mu\text{A}$                                         | $V_{(BR)}$   | 40                | -                 | -                  | V             |
| Reverse current<br>$V_R = 30\ \text{V}$                                                   | $I_R$        | -                 | -                 | 1                  | $\mu\text{A}$ |
| Forward voltage<br>$I_F = 1\ \text{mA}$<br>$I_F = 10\ \text{mA}$<br>$I_F = 40\ \text{mA}$ | $V_F$        | 250<br>350<br>600 | 310<br>450<br>720 | 380<br>500<br>1000 | mV            |
| Forward voltage matching <sup>1)</sup><br>$I_F = 10\ \text{mA}$                           | $\Delta V_F$ | -                 | -                 | 20                 |               |
| AC Characteristics                                                                        |              |                   |                   |                    |               |
| Diode capacitance<br>$V_R = 0$ , $f = 1\ \text{MHz}$                                      | $C_T$        | -                 | 3                 | 5                  | pF            |
| Differential forward resistance<br>$I_F = 10\ \text{mA}$ , $f = 10\ \text{kHz}$           | $R_F$        | -                 | 10                | -                  | $\Omega$      |
| Charge carrier life time<br>$I_F = 25\ \text{mA}$                                         | $\tau_{rr}$  | -                 | -                 | 100                | ps            |

<sup>1)</sup> $\Delta V_F$  is the difference between lowest and highest  $V_F$  in a multiple diode component.


**Diode capacitance  $C_T = f(V_R)$**

$f = 1\text{MHz}$




**Forward resistance  $r_f = f(I_F)$**

$f = 10\text{kHz}$




**Reverse current  $I_R = f(T_A)$**

$V_R = \text{Parameter}$




**Reverse current  $I_R = f(V_R)$**

$T_A = \text{Parameter}$




**Forward Voltage  $V_F = f(T_A)$**

$I_F$  = Parameter




**Forward current  $I_F = f(V_F)$**

$T_A$  = Parameter




**Forward current  $I_F = f(T_S)$**

BAS140W




**Forward current  $I_F = f(T_S)$**

BAS40, BAS40-07




**Forward current  $I_F = f(T_S)$**

BAS40-02L




**Forward current  $I_F = f(T_S)$**

BAS40-04, BAS40-06




**Forward current  $I_F = f(T_S)$**





BAS40-06W



**Forward current  $I_F = f(T_S)$**


BAS40-05



**Forward current  $I_F = f(T_S)$** 
**BAS40-05W**

**Forward current  $I_F = f(T_S)$** 
**BAS40-07W**

**Permissible Puls Load  $R_{thJS} = f(t_p)$** 
**BAS140W**

**Permissible Pulse Load**
 **$I_{Fmax}/I_{FDC} = f(t_p)$** 
**BAS140W**


**Permissible Puls Load  $R_{thJS} = f(t_p)$**


BAS40-02L



**Permissible Pulse Load**


$$I_{Fmax}/I_{FDC} = f(t_p)$$

BAS40-02L



**Permissible Puls Load  $R_{thJS} = f(t_p)$**


BAS40-06W



**Permissible Pulse Load**


$$I_{Fmax}/I_{FDC} = f(t_p)$$

BAS40-06W



### Permissible Puls Load $R_{thJS} = f(t_p)$


BAS40-05W




### Permissible Pulse Load

$$I_{Fmax}/I_{FDC} = f(t_p)$$


BAS40-05W




## Package Outline



## Foot Print




## Marking Layout (Example)




## Standard Packing


Reel  $\varnothing 180$  mm = 3.000 Pieces/Reel  
 Reel  $\varnothing 330$  mm = 10.000 Pieces/Reel




## Package Outline



## Foot Print




## Marking Layout (Example)




## Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel  
Reel ø330 mm = 10.000 Pieces/Reel




## Package Outline




1) Lead width can be 0.6 max. in dambar area

## Foot Print




## Marking Layout (Example)




## Standard Packing


Reel ø180 mm = 3.000 Pieces/Reel  
Reel ø330 mm = 10.000 Pieces/Reel




## Package Outline



## Foot Print




## Marking Layout (Example)




## Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel  
 Reel ø330 mm = 10.000 Pieces/Reel




## Package Outline




## Foot Print

For board assembly information please refer to Infineon website "Packages"




## Marking Layout (Example)



## Standard Packing

Reel  $\varnothing$ 180 mm = 15.000 Pieces/Reel  
Reel  $\varnothing$ 330 mm = 50.000 Pieces/Reel (optional)



**Edition 2009-11-16**

**Published by  
Infineon Technologies AG  
81726 Munich, Germany**

**© 2009 Infineon Technologies AG  
All Rights Reserved.**

### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([<www.infineon.com>](http://www.infineon.com)).

### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.