
N-Channel 30-V (D-S) MOSFET with Schottky Diode

MOSFET PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
30	0.0135 @ V_{GS} = 10 V	10
	0.020 @ V_{GS} = 4.5 V	8

SCHOTTKY PRODUCT SUMMARY		
V_{DS} (V)	V_{SD} (V) Diode Forward Voltage	I_F (A)
30	0.53 V @ 3.0 A	4.0

LITTLE FOOT Plus™


SO-8



Top View

Ordering Information:

Si4810DY
Si4810DY-T1 (with Tape and Reel)



ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage (MOSFET)		V_{DS}	30	V
Reverse Voltage (Schottky)			30	
Gate-Source Voltage (MOSFET)		V_{GS}	±20	
Continuous Drain Current (T_J = 150°C) (MOSFET)[a, b]	T_A = 25°C	I_D	10	A
	T_A = 70°C		8	
Pulsed Drain Current (MOSFET)		I_{DM}	50	
Continuous Source Current (MOSFET Diode Conduction)[a, b]		I_S	2.3	
Average Foward Current (Schottky)		I_F	4.0	
Pulsed Foward Current (Schottky)		I_{FM}	50	
Maximum Power Dissipation (MOSFET)[a, b]	T_A = 25°C	P_D	2.5	W
	T_A = 70°C		1.6	
Maximum Power Dissipation (Schottky)[a, b]	T_A = 25°C		2.0	
	T_A = 70°C		1.3	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS					
Parameter	Device	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient (t ≤ 10 sec)[a]	MOSFET	R_{thJA}		50	°C/W
	Schottky			60	
Maximum Junction-to-Ambient (t = steady state)[a]	MOSFET		70		
	Schottky		80		

Notes
a. Surface Mounted on FR4 Board.
b. t ≤ 10 sec.


For SPICE model information via the Worldwide Web: http://www.vishay.com/www/product/spice.htm

MOSFET + SCHOTTKY SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)						
Parameter	**Symbol**	**Test Condition**	**Min**	**Typ**	**Max**	**Unit**
Static						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 μA	1			V
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current (MOSFET + Schottky)	I_{DSS}	V_{DS} = 30 V, V_{GS} = 0 V		0.007	0.100	mA
		V_{DS} = 30 V, V_{GS} = 0 V, T_J = 100°C		1.5	10	
		V_{DS} = 30 V, V_{GS} = 0 V, T_J = 125°C		6.5	20	
On-State Drain Current[a]	$I_{D(on)}$	V_{DS} ≥ 5 V, V_{GS} = 10 V	20			A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = 10 V, I_D = 10 A		0.0105	0.0135	Ω
		V_{GS} = 4.5 V, I_D = 5 A		0.0155	0.020	
Forward Transconductance[a]	g_{fs}	V_{DS} = 15 V, I_D = 10 A		28		S
Schottky Diode Forward Voltage[a]	V_{SD}	I_S = 3.0 A, V_{GS} = 0 V		0.485	0.53	V
		I_S = 3.0 A, V_{GS} = 0 V, T_J = 125°C		0.420	0.47	
Dynamic[b]						
Total Gate Charge	Q_g	V_{DS} = 15 V, V_{GS} = 5 V, I_D = 10 A		20	30	nC
Gate-Source Charge	Q_{gs}			8		
Gate-Drain Charge	Q_{gd}			7		
Gate Resistance	R_g		0.5	1.0	1.6	Ω
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 15 V, R_L = 15 Ω I_D ≅ 1 A, V_{GEN} = 10 V, R_G = 6 Ω		15	30	ns
Rise Time	t_r			8	15	
Turn-Off Delay Time	$t_{d(off)}$			45	90	
Fall Time	t_f			18	40	
Source-Drain Reverse Recovery Time	t_{rr}	I_F = 3.0 A, di/dt = 100 A/μs		36	70	


Notes
a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance



Gate Charge




On-Resistance vs. Junction Temperature




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Reverse Current (Schottky)




Single Pulse Power



Normalized Thermal Transient Impedance, Junction-to-Ambient



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.