
Digital transistors (built-in resistor)

DTC144GE / DTC144GUA / DTC144GKA / DTC144GSA

●Features

1) The built-in bias resistors consist of thin-film resistors with complete isolation to allow negative biasing of the input, and parasitic effects are almost completely eliminated.
2) Only the on / off conditions need to be set for operation, making device design easy.
3) Higher mounting densities can be achieved.

●Circuit schematic



●Absolute maximum ratings (Ta=25°C)

Parameter		Symbol	Limits	Unit
Collector-base voltage		V_{CBO}	50	V
Collector-emitter voltage		V_{CEO}	50	V
Emitter-base voltage		V_{EBO}	5	V
Collector current		I_C	100	mA
Collector Power dissipation	DTC144GE	Pc	150	mW
	DTC144GUA / DTC144GKA		200	
	DTC144GSA		300	
Junction temperature		Tj	150	℃
Storage temperature		Tstg	–55 to +150	℃

●Package, marking, and packaging specifications

Part No.	DTC144GE	DTC144GUA	DTC144GKA	DTC144GSA
Package	EMT3	UMT3	SMT3	SPT
Marking	K26	K26	K26	–
Packaging code	TL	T106	T146	TP
Basic ordering unit (pieces)	3000	3000	3000	5000

●**Electrical characteristics** (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	50	–	–	V	I_C=50μA
Collector-emitter breakdown voltage	BV_{CEO}	50	–	–	V	I_C=1mA
Emitter-base breakdown voltage	BV_{EBO}	5	–	–	V	I_E=160μA
Collector cutoff current	I_{CBO}	–	–	0.5	μA	V_{CB}=50V
Emitter cutoff current	I_{EBO}	65	–	130	μA	V_{EB}=4V
Collector-emitter saturation voltage	$V_{CE(sat)}$	–	–	0.3	V	I_C=10mA , I_B=0.5mA
DC current transfer ratio	h_{FE}	68	–	–	–	I_C=5mA , V_{CE}=5V
Emitter-base resistance	R	32.9	47	61.1	kΩ	–
Transition frequency	f_T	–	250	–	MHz	V_{CE}=10V , I_E= –5mA , f=100MHz ＊

＊ Transition frequency of the device.

●**Electrical characteristics curves**




Fig.1 DC current gain vs. Collector current




Fig.2 Collector-Emitter saturation voltage vs. Collector current

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).
Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.
In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.