
PNP Silicon AF Transistors



- For general AF applications
- High collector current
- High current gain
- Low collector-emitter saturation voltage
- Complementary type: BCX68 (NPN)
- Pb-free (RoHS compliant) package [1)]
- Qualified according AEC Q101

AEC Qualified RoHS

Type	Marking	Pin Configuration			Package
BCX69-10	CF	1=B	2=C	3=E	SOT89
BCX69-16	CG	1=B	2=C	3=E	SOT89
BCX69-25	CH	1=B	2=C	3=E	SOT89

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CEO}	20	V
Collector-base voltage	V_{CBO}	25	
Emitter-base voltage	V_{EBO}	5	
Collector current	I_C	1	A
Peak collector current, $t_p \leq 10$ ms	I_{CM}	2	
Base current	I_B	100	mA
Peak base current	I_{BM}	200	
Total power dissipation- T_S = 114 °C	P_{tot}	3	W
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[2)]	R_{thJS}	≤ 12	K/W

[1]Pb-containing package may be available upon special request
[2]For calculation of R_{thJA} please refer to Application Note Thermal Resistance


Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Collector-emitter breakdown voltage I_C = 30 mA, I_B = 0	$V_{(BR)CEO}$	20	-	-	V
Collector-base breakdown voltage I_C = 10 µA, I_E = 0	$V_{(BR)CBO}$	25	-	-	
Emitter-base breakdown voltage I_E = 1 µA, I_C = 0	$V_{(BR)EBO}$	5	-	-	
Collector-base cutoff current	I_{CBO}				µA
V_{CB} = 25 V, I_E = 0		-	-	0.1	
V_{CB} = 25 V, I_E = 0 , T_A = 150		-	-	100	
DC current gain[1)]	h_{FE}				-
I_C = 5 mA, V_{CE} = 10 V		50	-	-	
I_C = 500 mA, V_{CE} = 1 V, BCX69-10		85	100	160	
I_C = 500 mA, V_{CE} = 1 V, BCX69-16		100	160	250	
I_C = 500 mA, V_{CE} = 1 V, BCX69-25		160	250	375	
I_C = 1 A, V_{CE} = 1 V		60	-	-	
Collector-emitter saturation voltage[1)] I_C = 1 A, I_B = 100 mA	V_{CEsat}	-	-	0.5	V
Base-emitter voltage[1)]	$V_{BE(ON)}$				
I_C = 5 mA, V_{CE} = 10 V		-	0.6	-	
I_C = 1 A, V_{CE} = 1 V		-	-	1	
AC Characteristics					
Transition frequency I_C = 100 mA, V_{CE} = 5 V, f = 20 MHz	f_T	-	100	-	MHz

[1]Pulse test: t < 300µs; D < 2%


DC current gain $h_{FE} = f(I_C)$

V_{CE} = 1 V




Collector-emitter saturation voltage

$I_C = f(V_{CEsat})$, h_{FE} = 10




Base-emitter saturation voltage

$I_C = f(V_{BEsat})$, h_{FE} = 10




Collector current $I_C = f(V_{BE})$

V_{CE} = 1V




Collector cutoff current $I_{CBO} = f(T_A)$

V_{CB} = 25 V




Transition frequency $f_T = f(I_C)$


V_{CE} = 5 V



Total power dissipation $P_{tot} = f(T_S)$




Permissible Pulse Load $R_{thJS} = f(t_p)$



Permissible Pulse Load

$P_{totmax}/P_{totDC} = f(t_p)$



Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.
Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.