
Power Transistor (100V, 2A)
2SD2195 / 2SD1980 / 2SD1867

●Features
1) Darlington connection for high DC current gain.
2) Built-in resistor between base and emitter.
3) Built-in damper diode.
4) Complements the 2SB1580 / 2SB1316.

●Equivalent circuit




●Absolute maximum ratings (Ta=25°C)

Parameter		Symbol	Limits	Unit
Collector-base voltage		VCBO	100	V
Collector-emitter voltage		VCEO	100	V
Emitter-base voltage		VEBO	6	V
Collector current		IC	2	A(DC)
			3 *1	A(Pulse)
Collector power dissipation	2SD2195	PC	0.5	W
			2 *2	
	2SD1980		1	W(Tc=25°C)
			10	
	2SD1867		1 *3	W
Junction temperature		Tj	150	°C
Storage temperature		Tstg	−55 to +150	°C

*1 Single pulse Pw=100ms
*2 When mounted on a 40 x 40 x 0.7 mm ceramic board.
*3 Printed circuit board, 1.7mm thick, collector plating 100mm² or larger.

●External dimensions (Unit : mm)


2SD2195



ROHM : MPT3
EIAJ : SC-62

(1) Base
(2) Collector
(3) Emitter


2SD1980



ROHM : CPT3
EIAJ : SC-63

(1) Base
(2) Collector
(3) Emitter

2SD1867



Taping specifications

ROHM : ATV

(1) Emitter
(2) Collector
(3) Base

●Packaging specifications and h_{FE}

Type	2SD2195	2SD1980	2SD1867
Package	MPT3	CPT3	ATV
h_{FE}	1k to 10k	1k to 10k	1k to 10k
Marking	DP	–	–
Code	T100	TL	TV2
Basic ordering unit (pieces)	1000	2500	2500

∗Denotes h_{FE}

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	100	–	–	V	I_C=50μA
Collector-emitter breakdown voltage	BV_{CBO}	100	–	–	V	I_C=5mA
Emitter-base breakdown voltage	BV_{EBO}	6	–	–	V	I_E=5mA
Collector cutoff current	I_{CBO}	–	–	10	μA	V_{CB}=100V
Emitter cutoff current	I_{EBO}	–	–	3	mA	V_{EB}=5V
Collector-emitter saturation voltag	$V_{CE(sat)}$	–	–	1.5	V	I_C=1A, I_B=1mA ∗
Base-Emitter saturation voltage	$V_{BE(sat)}$	–	–	2.0	V	I_C/I_B=1A/1mA
DC current transfer ratio	h_{FE}	1000	–	10000	–	V_{CE}=2V, I_C=1A ∗
Transition frequency	f_T	–	80	–	MHz	V_{CE}=5V, I_E=–0.1A, f=30MHz
Output capacitance	Cob	–	25	–	pF	V_{CB}=10V, I_E=0A, f=1MHz

∗Measured using pulse current.

●Electrical characteristic curves




Fig.1 Grounded emitter output characteristics




Fig.2 Grounded emitter propagation characteristics




Fig.3 DC current gain vs. collector current




Fig.4 DC current gain vs. collector current




Fig.5 Collector-emitter saturation voltage vs.collector current




Fig.6 Collector-emitter saturation voltage vs.collector current




Fig.7 Collector output capacitance vs. collector-base voltage




Fig.8 Safe operating area (2SD2195)




Fig.9 Safe operating area(2SD1867)

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).
Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.
In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.