Dual P-Channel 12-V (D-S) MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
–12	0.370 @ V_{GS} = –4.5 V	–1.15
	0.575 @ V_{GS} = –2.5 V	–0.92
	0.800 @ V_{GS} = –1.8 V	–0.78


FEATURES

- TrenchFET® Power MOSFETS: 1.8-V Rated
- ESD Protected: 3000 V
- Thermally Enhanced SC-70 Package


APPLICATIONS


- Load Switching
- PA Switch
- Level Switch


SOT-363
SC-70 (6-LEADS)



Top View







ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)					
Parameter		Symbol	5 secs	Steady State	Unit
Drain-Source Voltage		V_{DS}	–12		V
Gate-Source Voltage		V_{GS}	±12		
Continuous Drain Current (T_J = 150°C)[a]	T_A = 25°C	I_D	–1.15	–1.00	A
	T_A = 85°C		–0.83	–0.73	
Pulsed Drain Current		I_{DM}	–3		
Continuous Diode Current (Diode Conduction)[a]		I_S	–0.61	–0.47	
Maximum Power Dissipation[a]	T_A = 25°C	P_D	0.73	0.57	W
	T_A = 85°C		0.38	0.30	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	–55 to 150		°C

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient[a]	t ≤ 5 sec	R_{thJA}	130	170	°C/W
	Steady State		170	220	
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	80	100	


Notes
a. Surface Mounted on 1" x 1" FR4 Board.


SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = –100 µA	–0.45			V
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±4.5 V			±1.5	µA
		V_{DS} = 0 V, V_{GS} = ±12 V			±10	mA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = –9.6 V, V_{GS} = 0 V			–1	µA
		V_{DS} = –9.6 V, V_{GS} = 0 V, T_J = 85°C			–5	
On-State Drain Current[a]	$I_{D(on)}$	V_{DS} = –5 V, V_{GS} = –4.5 V	–2			A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = –4.5 V, I_D = –1.0 A		0.300	0.370	Ω
		V_{GS} = –2.5 V, I_D = –0.81 A		0.470	0.575	
		V_{GS} = –1.8 V, I_D = –0.2 A		0.660	0.800	
Forward Transconductance[a]	g_{fs}	V_{DS} = –10 V, I_D = –1.0 A		1.7		S
Diode Forward Voltage[a]	V_{SD}	I_S = –0.47 A, V_{GS} = 0 V		–0.85	–1.2	V
Dynamic[b]						
Total Gate Charge	Q_g	V_{DS} = –6 V, V_{GS} = –4.5 V, I_D = –1.0 A		1.3	2.0	nC
Gate-Source Charge	Q_{gs}			0.31		
Gate-Drain Charge	Q_{gd}			0.31		
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = –6 V, R_L = 12 Ω I_D ≅ –0.5 A, V_{GEN} = –4.5 V, R_G = 6 Ω		0.17	0.26	µs
Rise Time	t_r			0.47	0.71	
Turn-Off Delay Time	$t_{d(off)}$			0.96	1.4	
Fall Time	t_f			1.0	1.5	

Notes
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.


TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Capacitance



Gate Charge




On-Resistance vs. Junction Temperature




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage




Single Pulse Power, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Ambient



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.