

IHW30N90T

Soft Switching Series

Low Loss DuoPack : IGBT in TrenchStop® and Fieldstop technology with anti-parallel diode





Features:

- 1.1V Forward voltage of antiparallel diode
- TrenchStop® and Fieldstop technology for 900 V applications offers :
  - very tight parameter distribution
  - high ruggedness, temperature stable behavior
  - easy parallel switching capability due to positive temperature coefficient in $V_{CE(sat)}$
- Low EMI
- Qualified according to JEDEC[1] for target applications
- Application specific optimisation of inverse diode
- Pb-free lead plating; RoHS compliant

Applications:

- Microwave Oven
- Soft Switching Applications for ZCS

Type	V_{CE}	I_C	$V_{CE(sat),Tj=25°C}$	$T_{j,max}$	Marking	Package
IHW30N90T	900V	30A	1.5V	175°C	H30T90	PG-TO-247-3

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CE}	900	V
DC collector current T_C = 25°C T_C = 100°C	I_C	 60 30	A
Pulsed collector current, t_p limited by T_{jmax}	I_{Cpuls}	90	
Turn off safe operating area $V_{CE} \le 900V$, $T_j \le 175°C$	-	90	
Diode forward current T_C = 25°C T_C = 100°C	I_F	 23 13	
Diode pulsed current, t_p limited by T_{jmax}	I_{Fpuls}	36	
Gate-emitter voltage Transient Gate-emitter voltage (t_p < 5 ms)	V_{GE}	±20 ±25	V
Power dissipation, T_C = 25°C	P_{tot}	428	W
Operating junction temperature	T_j	-40...+175	°C
Storage temperature	T_{stg}	-55...+175	°C
Soldering temperature, 1.6mm (0.063 in.) from case for 10s	-	260	

[1] J-STD-020 and JESD-022

Thermal Resistance

Parameter	Symbol	Conditions	Max. Value	Unit
Characteristic				
IGBT thermal resistance, junction – case	R_{thJC}		0.35	K/W
Diode thermal resistance, junction – case	R_{thJCD}		1.1	
Thermal resistance, junction – ambient	R_{thJA}		40	

Electrical Characteristic, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
Static Characteristic						
Collector-emitter breakdown voltage	$V_{(BR)CES}$	V_{GE}=0V, I_C=500µA	900	-	-	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	V_{GE} = 15V, I_C=30A				
		T_j=25°C	-	1.5	1.7	
		T_j=150°C	-	1.7	-	
		T_j=175°C	-	1.8	-	
Diode forward voltage	V_F	V_{GE}=0V, I_F=10A				
		T_j=25°C	-	1.1	1.3	
		T_j=150°C	-	1.0	-	
		T_j=175°C	-	1.0	-	
Gate-emitter threshold voltage	$V_{GE(th)}$	I_C=150µA, V_{CE}=V_{GE}	4.6	5.3	6	
Zero gate voltage collector current	I_{CES}	V_{CE}=900V, V_{GE}=0V				µA
		T_j=25°C	-	-	250	
		T_j=150°C	-	-	2500	
Gate-emitter leakage current	I_{GES}	V_{CE}=0V, V_{GE}=20V	-	-	600	nA
Transconductance	g_{fs}	V_{CE}=20V, I_C=20A	-	26	-	S
Dynamic Characteristic						
Input capacitance	C_{iss}	V_{CE}=25V,	-	2617	-	pF
Output capacitance	C_{oss}	V_{GE}=0V,	-	96	-	
Reverse transfer capacitance	C_{rss}	f=1MHz	-	38	-	
Gate charge	Q_{Gate}	V_{CC}=720V, I_C=30A V_{GE}=15V	-	280	-	nC
Internal emitter inductance measured 5mm (0.197 in.) from case	L_E		-	13	-	nH

Switching Characteristic, Inductive Load, at T_j=25 °C

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
IGBT Characteristic						
Turn-on delay time	$t_{d(on)}$	T_j=25°C,	-	45	-	ns
Rise time	t_r	V_{CC}=600V,I_C=30A,	-	26	-	
Turn-off delay time	$t_{d(off)}$	V_{GE}=0/15V,	-	556	-	
Fall time	t_f	R_G=15Ω,	-	29	-	
Turn-on energy	E_{on}		-	-	-	mJ
Turn-off energy	E_{off}		-	1.8	-	
Total switching energy	E_{ts}		-	1.8	-	

Switching Characteristic, Inductive Load, at T_j=175 °C

Parameter	Symbol	Conditions	Value			Unit
			min.	Typ.	max.	
IGBT Characteristic						
Turn-on delay time	$t_{d(on)}$	T_j=175°C	-	44	-	ns
Rise time	t_r	V_{CC}=600V,	-	38	-	
Turn-off delay time	$t_{d(off)}$	I_C=30A,	-	650	-	
Fall time	t_f	V_{GE}=0/15V,	-	41	-	
Turn-on energy	E_{on}	R_G= 15Ω	-	-	-	mJ
Turn-off energy	E_{off}		-	2.4	-	
Total switching energy	E_{ts}		-	2.4	-	




Figure 1. Collector current as a function of switching frequency for triangular current (E_{on} = 0, hard turn-off)
($T_j \le 175°C$, $D = 0.5$, $V_{CE} = 600V$, $V_{GE} = 0/+15V$, $R_G = 15\Omega$)




Figure 2. IGBT Safe operating area
($D = 0$, $T_C = 25°C$, $T_j \le 175°C$; V_{GE}=15V)




Figure 3. Power dissipation as a function of case temperature
($T_j \le 175°C$)




Figure 4. Collector current as a function of case temperature
($V_{GE} \ge 15V$, $T_j \le 175°C$)




Figure 5. Typical output characteristic
(T_j = 25°C)




Figure 6. Typical output characteristic
(T_j = 175°C)




Figure 7. Typical transfer characteristic
(V_{CE}=20V)




Figure 8. Typical collector-emitter saturation voltage as a function of junction temperature
(V_{GE} = 15V)




Figure 9. Typical switching times as a function of collector current
(inductive load, T_J=175°C, V_{CE}=600V, V_{GE}=0/15V, R_G=15Ω, Dynamic test circuit in Figure E)




Figure 10. Typical switching times as a function of gate resistor
(inductive load, T_J=175°C, V_{CE}=600V, V_{GE}=0/15V, I_C=30A, Dynamic test circuit in Figure E)




Figure 11. Typical switching times as a function of junction temperature
(inductive load, V_{CE}=600V, V_{GE}=0/15V, I_C=30A, R_G=15Ω, Dynamic test circuit in Figure E)




Figure 12. Gate-emitter threshold voltage as a function of junction temperature
(I_C = 0.3mA)




Figure 13. Typical switching energy losses as a function of collector current
(inductive load, T_J=175°C, V_{CE}=600V, V_{GE}=0/15V, R_G=15Ω, Dynamic test circuit in Figure E)




Figure 14. Typical switching energy losses as a function of gate resistor
(inductive load, T_J=175°C, V_{CE}=600V, V_{GE}=0/15V, I_C=30A, Dynamic test circuit in Figure E)




Figure 15. Typical switching energy losses as a function of junction temperature
(inductive load, V_{CE}=600V, V_{GE}=0/15V, I_C=30A, R_G=15Ω, Dynamic test circuit in Figure E)




Figure 16. Typical switching energy losses as a function of collector emitter voltage
(inductive load, T_J=175°C, V_{GE}=0/15V, I_C=30A, R_G=15Ω, Dynamic test circuit in Figure E)




Figure 17. Typical gate charge
(I_C=30 A)




Figure 18. Typical capacitance as a function of collector-emitter voltage
(V_{GE}=0V, f = 1 MHz)




Figure 19. IGBT transient thermal resistance
($D = t_p / T$)




Figure 20. Typical Diode transient thermal impedance as a function of pulse width
($D=t_P/T$)




Figure 21. Typical diode forward current as a function of forward voltage





Figure 22. Typical diode forward voltage as a function of junction temperature

PG-TO247-3



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.90	5.16	0.193	0.203
A1	2.27	2.53	0.089	0.099
A2	1.85	2.11	0.073	0.083
b	1.07	1.33	0.042	0.052
b1	1.90	2.41	0.075	0.095
b2	1.90	2.16	0.075	0.085
b3	2.87	3.38	0.113	0.133
b4	2.87	3.13	0.113	0.123
c	0.55	0.68	0.022	0.027
D	20.82	21.10	0.820	0.831
D1	16.25	17.65	0.640	0.695
D2	1.05	1.35	0.041	0.053
E	15.70	16.03	0.618	0.631
E1	13.10	14.15	0.516	0.557
E2	3.68	5.10	0.145	0.201
E3	1.68	2.60	0.066	0.102
e	5.44		0.214	
N	3		3	
L	19.80	20.31	0.780	0.799
L1	4.17	4.47	0.164	0.176
øP	3.50	3.70	0.138	0.146
Q	5.49	6.00	0.216	0.236
S	6.04	6.30	0.238	0.248

DOCUMENT NO.
Z8B00003327

SCALE 0 5 5 7.5mm

EUROPEAN PROJECTION

ISSUE DATE
17-12-2007

REVISION
03




Figure A. Definition of switching times




Figure B. Definition of switching losses




Figure C. Definition of diodes switching characteristics




Figure D. Thermal equivalent circuit

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.