

---

### LOW NOISE 150mA LDO REGULATOR

---

NO.EA-173-131031

#### OUTLINE

The RP130x Series are CMOS-based positive voltage regulator ICs with high ripple rejection, low dropout voltage, high output voltage accuracy and extremely low supply current. Each of these ICs consists of a voltage reference unit, an error amplifier, a resistor-net for voltage setting, a short current limit circuit and a chip enable circuit.

These ICs have an excellent low supply current performed by CMOS process, moreover they perform with low dropout voltage due to built-in low ON-resistance. A chip enable function prolongs the battery life.

The input transient response, the load transient response and the ripple rejection have been improved in the RP130x Series compared with the conventional products. Besides achieving low supply current (Typ.38 $\mu$ A).

The range of the operation voltage is capable from 1.7V to 6.5V and the range of the output voltage is capable from 1.2V to 5.3V for this product, which is wider range as our conventional product R1114x series.




The output voltage of these ICs is fixed with high accuracy. Since the packages for these ICs are DFN(PLP)1010-4, SOT-23-5 and SC-82AB, therefore high density mounting of the ICs on boards is possible.

#### FEATURES

- Supply Current ..... Typ. 38 $\mu$ A
- Supply Current (Standby Mode) ..... Typ. 0.1  $\mu$ A
- Ripple Rejection..... Typ. 80dB (f=1kHz)
- Input Voltage Range ..... 1.7V to 6.5V
- Output Voltage Range ..... 1.2V to 5.3V (0.1V steps)  
(For other voltages, please refer to MARK INFORMATION.)
- Output Voltage Accuracy .....  $\pm 1.0\%$  ( $V_{OUT}>2.0V$ ,  $T_{opt}=25^{\circ}C$ )
- Temperature-Drift Coefficient of Output Voltage ..... Typ.  $\pm 20ppm/^{\circ}C$
- Dropout Voltage ..... Typ. 0.32V ( $I_{OUT}=150mA$ ,  $V_{OUT}=2.8V$ )
- Line Regulation ..... Typ. 0.02%/V
- Packages ..... DFN(PLP)1010-4, SC-82AB, SOT-23-5
- Built-in Fold Back Protection Circuit ..... Typ. 40mA
- Ceramic capacitors are recommended to be used with this IC .....0.47 $\mu$ F or more

#### APPLICATIONS

- Power source for battery-powered equipment.
- Power source for portable communication equipment.
- Power source for electrical appliances such as cameras, VCRs and camcorders.
- Power source for high stable reference voltage.

**BLOCK DIAGRAMS**

## SELECTION GUIDE

The output voltage, chip enable polarity, auto discharge function, and package, etc. for the ICs can be selected at the user's request.

| Product Name     | Package        | Quantity per Reel | Pb Free | Halogen Free |
|------------------|----------------|-------------------|---------|--------------|
| RP130Kxx1*-TR    | DFN(PLP)1010-4 | 10,000 pcs        | Yes     | Yes          |
| RP130Qxx1*-TR-FE | SC-82AB        | 3,000 pcs         | Yes     | Yes          |
| RP130Nxx1*-TR-FE | SOT-23-5       | 3,000 pcs         | Yes     | Yes          |

xx : Set Output Voltage ( $V_{SET}$ )

Fixed Type: 12 to 53 Stepwise setting with 0.1V increment in the range from 1.2V to 5.3V

Exception: 1.25V=RP130x121\*5-TR

1.85V=RP130x181\*5-TR

2.85V=RP130x281\*5-TR


\* : CE pin polarity and auto discharge function at off state are options as follows.

A: active low, without auto discharge function at off state.

B: active high, without auto discharge function at off state.

D: active high, with auto discharge function at off state.

PIN CONFIGURATIONS



PIN DESCRIPTIONS

• DFN(PLP)1010-4

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | V <sub>OUT</sub>            | Output Pin                                |
| 2      | GND                         | Ground Pin                                |
| 3      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 4      | V <sub>DD</sub>             | Input Pin                                 |

\*) Tab is GND level. (They are connected to the reverse side of this IC.)  
The tab is better to be connected to the GND, but leaving it open is also acceptable.

• SC-82AB

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 2      | GND                         | Ground Pin                                |
| 3      | V <sub>OUT</sub>            | Output Pin                                |
| 4      | V <sub>DD</sub>             | Input Pin                                 |

• SOT-23-5

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | V <sub>DD</sub>             | Input Pin                                 |
| 2      | GND                         | Ground Pin                                |
| 3      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 4      | NC                          | No Connection                             |
| 5      | V <sub>OUT</sub>            | Output Pin                                |

## ABSOLUTE MAXIMUM RATINGS

| Symbol    | Item                                | Rating               | Unit |
|-----------|-------------------------------------|----------------------|------|
| $V_{IN}$  | Input Voltage                       | 7.0                  | V    |
| $V_{CE}$  | Input Voltage (CE Pin)              | −0.3 to 7.0          | V    |
| $V_{OUT}$ | Output Voltage                      | −0.3 to $V_{IN}+0.3$ | V    |
| $I_{OUT}$ | Output Current                      | 200                  | mA   |
| $P_D$     | Power Dissipation (DFN(PLP)1010-4)* | 400                  | mW   |
|           | Power Dissipation (SC-82AB)*        | 380                  |      |
|           | Power Dissipation (SOT-23-5)*       | 420                  |      |
| $T_{opt}$ | Operating Temperature Range         | −40 to 85            | °C   |
| $T_{stg}$ | Storage Temperature Range           | −55 to 125           | °C   |

\*) For Power Dissipation, please refer to PACKAGE INFORMATION.

### ABSOLUTE MAXIMUM RATINGS

Electronic and mechanical stress momentarily exceeded absolute maximum ratings may cause the permanent damages and may degrade the life time and safety for both device and system using the device in the field.

The functional operation at or over these absolute maximum ratings is not assured.

## RP130x

NO.EA-173-131031

## ELECTRICAL CHARACTERISTICS

$V_{IN}=V_{SET}+1V$  ( $V_{OUT}>1.5V$ ),  $V_{IN}=2.5V$  ( $V_{OUT}\leq 1.5V$ ),  $I_{OUT}=1mA$ ,  $C_{IN}=C_{OUT}=0.47\mu F$ , unless otherwise noted.

The specifications surrounded by   are guaranteed by Design Engineering at  $-40^{\circ}C \leq T_a \leq 85^{\circ}C$ .

### ● RP130xxx1A

( $T_a=25^{\circ}C$ )

| Symbol                                  | Item                                   | Conditions                                                                                                                | Min.                                                              | Typ.                                                                  | Max.                                                                  | Unit             |
|-----------------------------------------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|------------------|
| $V_{OUT}$                               | Output Voltage                         | $T_a=25^{\circ}C$                                                                                                         | $V_{SET} > 2.0V$                                                  | x 0.99                                                                | x 1.01                                                                | V                |
|                                         |                                        |                                                                                                                           | $V_{SET} \leq 2.0V$                                               | -20                                                                   | +20                                                                   | mV               |
|                                         |                                        | $-40^{\circ}C \leq T_a \leq 85^{\circ}C$                                                                                  | $V_{SET} > 2.0V$                                                  | <span style="border: 1px solid black; padding: 0 2px;">x 0.985</span> | <span style="border: 1px solid black; padding: 0 2px;">x 1.015</span> | V                |
|                                         |                                        |                                                                                                                           | $V_{SET} \leq 2.0V$                                               | <span style="border: 1px solid black; padding: 0 2px;">-30</span>     | <span style="border: 1px solid black; padding: 0 2px;">+30</span>     | mV               |
| $I_{LIM}$                               | Output Current Limit                   |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">150</span> |                                                                       |                                                                       | mA               |
| $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ | Load Regulation                        | $1mA \leq I_{OUT} \leq 150mA$                                                                                             |                                                                   | 10                                                                    | <span style="border: 1px solid black; padding: 0 2px;">30</span>      | mV               |
| $V_{DIF}$                               | Dropout Voltage                        | Please see the table (Dropout Voltage) on below page.                                                                     |                                                                   |                                                                       |                                                                       |                  |
| $I_{SS}$                                | Supply Current                         | $I_{OUT}=0mA$                                                                                                             |                                                                   | 38                                                                    | <span style="border: 1px solid black; padding: 0 2px;">58</span>      | $\mu A$          |
| $I_{standby}$                           | Supply Current (Standby)               | $V_{CE}=V_{IN}$                                                                                                           |                                                                   | 0.1                                                                   | 1.0                                                                   | $\mu A$          |
| $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$  | Line Regulation                        | $V_{SET}+0.5V \leq V_{IN} \leq 6.5V$                                                                                      |                                                                   | 0.02                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.10</span>    | %/V              |
| RR                                      | Ripple Rejection                       | $f=1kHz$ , Ripple 0.2Vp-p<br>$V_{IN}=V_{SET}+1V$<br>$I_{OUT}=30mA$<br>(In case that $V_{OUT} \leq 2.0V$ , $V_{IN}=3.0V$ ) |                                                                   | 80                                                                    |                                                                       | dB               |
| $V_{IN}$                                | Input Voltage                          |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">1.7</span> |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">6.5</span>     | V                |
| $\frac{\Delta V_{OUT}}{\Delta T_a}$     | Output Voltage Temperature Coefficient | $-40^{\circ}C \leq T_a \leq 85^{\circ}C$                                                                                  |                                                                   | $\pm 20$                                                              |                                                                       | ppm/ $^{\circ}C$ |
| $I_{SC}$                                | Short Current Limit                    | $V_{OUT}=0V$                                                                                                              |                                                                   | 40                                                                    |                                                                       | mA               |
| $V_{CEH}$                               | $\overline{CE}$ Input Voltage "H"      |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">1.0</span> |                                                                       |                                                                       | $\mu A$          |
| $V_{CEL}$                               | $\overline{CE}$ Input Voltage "L"      |                                                                                                                           |                                                                   |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">0.4</span>     |                  |
| en                                      | Output Noise                           | BW=10Hz to 100kHz<br>$I_{OUT}=30mA$                                                                                       |                                                                   | 20<br>x $V_{SET}$                                                     |                                                                       | $\mu V_{rms}$    |

All test items listed under *Electrical Characteristics* are done under the pulse load condition ( $T_j \approx T_a=25^{\circ}C$ ) except for Output Noise, Ripple Rejection, and Output Voltage Temperature Coefficient.

$V_{IN}=V_{SET}+1V$  ( $V_{OUT}>1.5V$ ),  $V_{IN}=2.5V$  ( $V_{OUT}\leq 1.5V$ ),  $I_{OUT}=1mA$ ,  $C_{IN}=C_{OUT}=0.47\mu F$ , unless otherwise noted.

The specifications surrounded by   are guaranteed by Design Engineering at  $-40^{\circ}C \leq Ta \leq 85^{\circ}C$ .

● RP130xxx1B/D

( $Ta=25^{\circ}C$ )

| Symbol                                  | Item                                                  | Conditions                                                                                                                | Min.                                                              | Typ.                                                                  | Max.                                                                  | Unit             |
|-----------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|------------------|
| $V_{OUT}$                               | Output Voltage                                        | $Ta=25^{\circ}C$                                                                                                          | $V_{SET} > 2.0V$                                                  | x 0.99                                                                | x 1.01                                                                | V                |
|                                         |                                                       |                                                                                                                           | $V_{SET} \leq 2.0V$                                               | -20                                                                   | +20                                                                   | mV               |
|                                         |                                                       | $-40^{\circ}C \leq Ta \leq 85^{\circ}C$                                                                                   | $V_{SET} > 2.0V$                                                  | <span style="border: 1px solid black; padding: 0 2px;">x 0.985</span> | <span style="border: 1px solid black; padding: 0 2px;">x 1.015</span> | V                |
|                                         |                                                       |                                                                                                                           | $V_{SET} \leq 2.0V$                                               | <span style="border: 1px solid black; padding: 0 2px;">-30</span>     | <span style="border: 1px solid black; padding: 0 2px;">+30</span>     | mV               |
| $I_{LIM}$                               | Output Current Limit                                  |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">150</span> |                                                                       |                                                                       | mA               |
| $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ | Load Regulation                                       | $1mA \leq I_{OUT} \leq 150mA$                                                                                             |                                                                   | 10                                                                    | <span style="border: 1px solid black; padding: 0 2px;">30</span>      | mV               |
| $V_{DIF}$                               | Dropout Voltage                                       | Please see the table (Dropout Voltage) on next page.                                                                      |                                                                   |                                                                       |                                                                       |                  |
| $I_{SS}$                                | Supply Current                                        | $I_{OUT}=0mA$                                                                                                             |                                                                   | 38                                                                    | <span style="border: 1px solid black; padding: 0 2px;">58</span>      | $\mu A$          |
| $I_{standby}$                           | Supply Current (Standby)                              | $V_{CE}=V_{IN}$                                                                                                           |                                                                   | 0.1                                                                   | 1.0                                                                   | $\mu A$          |
| $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$  | Line Regulation                                       | $V_{SET}+0.5V \leq V_{IN} \leq 6.5V$                                                                                      |                                                                   | 0.02                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.10</span>    | %/V              |
| RR                                      | Ripple Rejection                                      | $f=1kHz$ , Ripple 0.2Vp-p<br>$V_{IN}=V_{SET}+1V$<br>$I_{OUT}=30mA$<br>(In case that $V_{OUT} \leq 2.0V$ , $V_{IN}=3.0V$ ) |                                                                   | 80                                                                    |                                                                       | dB               |
| $V_{IN}$                                | Input Voltage                                         |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">1.7</span> |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">6.5</span>     | V                |
| $\frac{\Delta V_{OUT}}{\Delta Ta}$      | Output Voltage Temperature Coefficient                | $-40^{\circ}C \leq Ta \leq 85^{\circ}C$                                                                                   |                                                                   | $\pm 20$                                                              |                                                                       | ppm/ $^{\circ}C$ |
| $I_{SC}$                                | Short Current Limit                                   | $V_{OUT}=0V$                                                                                                              |                                                                   | 40                                                                    |                                                                       | mA               |
| $I_{PD}$                                | CE Pull-down Current                                  |                                                                                                                           |                                                                   | 0.4                                                                   |                                                                       | $\mu A$          |
| $V_{CEH}$                               | $\overline{CE}$ Input Voltage "H"                     |                                                                                                                           | <span style="border: 1px solid black; padding: 0 2px;">1.0</span> |                                                                       |                                                                       | $\mu A$          |
| $V_{CEL}$                               | $\overline{CE}$ Input Voltage "L"                     |                                                                                                                           |                                                                   |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">0.4</span>     |                  |
| en                                      | Output Noise                                          | $BW=10Hz$ to $100kHz$<br>$I_{OUT}=30mA$                                                                                   |                                                                   | 20<br>x $V_{SET}$                                                     |                                                                       | $\mu V_{rms}$    |
| $R_{LOW}$                               | Nch ON Resistance for Auto Discharge (D version Only) | $V_{IN}=4.0V$<br>$V_{CE}=0V$                                                                                              |                                                                   | 30                                                                    |                                                                       | $\Omega$         |

All test items listed under *Electrical Characteristics* are done under the pulse load condition ( $T_j \approx Ta=25^{\circ}C$ ) except for Output Noise, Ripple Rejection, and Output Voltage Temperature Coefficient.

The specifications surrounded by   are guaranteed by Design Engineering at  $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$ .

## Dropout Voltage


( $T_a=25^{\circ}\text{C}$ )

| Output Voltage<br>$V_{\text{OUT}}$ (V)          | Dropout Voltage<br>$V_{\text{DIF}}$ (V) |      |                                                                    |
|-------------------------------------------------|-----------------------------------------|------|--------------------------------------------------------------------|
|                                                 | Condition                               | TYP. | MAX.                                                               |
| $1.2\text{V} \leq V_{\text{SET}} < 1.5\text{V}$ | $I_{\text{OUT}} = 150\text{mA}$         | 0.67 | <span style="border: 1px solid black; padding: 0 2px;">1.00</span> |
| $1.5\text{V} \leq V_{\text{SET}} < 1.7\text{V}$ |                                         | 0.54 | <span style="border: 1px solid black; padding: 0 2px;">0.81</span> |
| $1.7\text{V} \leq V_{\text{SET}} < 2.0\text{V}$ |                                         | 0.46 | <span style="border: 1px solid black; padding: 0 2px;">0.68</span> |
| $2.0\text{V} \leq V_{\text{SET}} < 2.5\text{V}$ |                                         | 0.41 | <span style="border: 1px solid black; padding: 0 2px;">0.60</span> |
| $2.5\text{V} \leq V_{\text{SET}} < 4.0\text{V}$ |                                         | 0.32 | <span style="border: 1px solid black; padding: 0 2px;">0.51</span> |
| $4.0\text{V} \leq V_{\text{SET}}$               |                                         | 0.24 | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |

## RECOMMENDED OPERATING CONDITIONS (ELECTRICAL CHARACTERISTICS)

All of electronic equipment should be designed that the mounted semiconductor devices operate within the recommended operating conditions. The semiconductor devices cannot operate normally over the recommended operating conditions, even if when they are used over such conditions by momentary electronic noise or surge. And the semiconductor devices may receive serious damage when they continue to operate over the recommended operating conditions.

## TYPICAL APPLICATION



(External Components)

Ceramic Capacitor C2    0.47 $\mu$ F    MURATA    GRM155B30J474KE18B

## TECHNICAL NOTES

When using these ICs, consider the following points:

### Phase Compensation

In these ICs, phase compensation is made for securing stable operation even if the load current is varied. For this purpose, use a capacitor C2 with 0.47 $\mu$ F or more.

If a tantalum capacitor is used, and its ESR (Equivalent Series Resistance) of C2 is large, the loop oscillation may result. Because of this, select C2 carefully considering its frequency characteristics.

### PCB Layout

Make  $V_{DD}$  and GND lines sufficient. If their impedance is high, noise pickup or unstable operation may result. Connect a capacitor C1 with a capacitance value as much as 0.47 $\mu$ F or more between  $V_{DD}$  and GND pin, and as close as possible to the pins.

Set external components, especially the output capacitor C2, as close as possible to the ICs, and make wiring as short as possible.



PACKAGE INFORMATION

• Power Dissipation (DFN(PLP)1010-4)

Power Dissipation (P<sub>D</sub>) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:


|                        |                                               |
|------------------------|-----------------------------------------------|
| Measurement Conditions |                                               |
|                        | Standard Test Land Pattern                    |
| Environment            | Mounting on Board (Wind velocity=0m/s)        |
| Board Material         | Glass cloth epoxy plastic (Double sided)      |
| Board Dimensions       | 40mm x 40mm x 1.6mm                           |
| Copper Ratio           | Top side: Approx. 50%, Back side: Approx. 50% |
| Through-holes          | φ 0.54mm x 24pcs                              |

|                    |                                                                              |                        |
|--------------------|------------------------------------------------------------------------------|------------------------|
| Measurement Result |                                                                              | (Ta=25°C, Tjmax=125°C) |
|                    | Standard Test Land Pattern                                                   |                        |
| Power Dissipation  | 400mW(Tjmax=125°C)<br>500mW(Tjmax=150°C)                                     |                        |
| Thermal Resistance | $\theta_{ja} = (125-25^{\circ}\text{C})/0.4\text{W} = 250^{\circ}\text{C/W}$ |                        |
|                    | $\theta_{jc}=67^{\circ}\text{C/W}$                                           |                        |



The above graph shows the Power Dissipation of the package based on Tjmax=125°C and Tjmax=150°C. Operating the IC in the shaded area in the graph might have an influence it's lifetime. Operating time must be within the time limit described in the table below, in case of operating in the shaded area.


|                |                                               |
|----------------|-----------------------------------------------|
| Operating Time | Estimated years<br>(Operating four hours/day) |
| 13,000 hours   | 9years                                        |



(Unit : mm)

The tab is better to be connected to the GND, but leaving it open is also acceptable.

- ①②: Product Code ... **Please refer to RP130K Series Mark Specification Table**  
③④: Lot Number ... Alphanumeric Serial Number



## RP130x

NO.EA-173-131031

### ● RP130K Series Mark Specification Table (DFN(PLP)1010-4)

RP130Kxx1A

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130K121A  | RA | 1.2V             |
| RP130K131A  | RB | 1.3V             |
| RP130K141A  | RC | 1.4V             |
| RP130K151A  | RD | 1.5V             |
| RP130K161A  | RE | 1.6V             |
| RP130K171A  | RF | 1.7V             |
| RP130K181A  | RG | 1.8V             |
| RP130K191A  | RJ | 1.9V             |
| RP130K201A  | RK | 2.0V             |
| RP130K211A  | RL | 2.1V             |
| RP130K221A  | RM | 2.2V             |
| RP130K231A  | RN | 2.3V             |
| RP130K241A  | RP | 2.4V             |
| RP130K251A  | RQ | 2.5V             |
| RP130K261A  | RR | 2.6V             |
| RP130K271A  | RS | 2.7V             |
| RP130K281A  | RT | 2.8V             |
| RP130K291A  | RV | 2.9V             |
| RP130K301A  | RW | 3.0V             |
| RP130K311A  | RX | 3.1V             |
| RP130K321A  | RY | 3.2V             |
| RP130K331A  | RZ | 3.3V             |
| RP130K341A  | SA | 3.4V             |
| RP130K351A  | SB | 3.5V             |
| RP130K361A  | SC | 3.6V             |
| RP130K371A  | SD | 3.7V             |
| RP130K381A  | SE | 3.8V             |
| RP130K391A  | SF | 3.9V             |
| RP130K401A  | SG | 4.0V             |
| RP130K411A  | SH | 4.1V             |
| RP130K421A  | SJ | 4.2V             |
| RP130K431A  | SK | 4.3V             |
| RP130K441A  | SL | 4.4V             |
| RP130K451A  | SM | 4.5V             |
| RP130K461A  | SN | 4.6V             |
| RP130K471A  | SP | 4.7V             |
| RP130K481A  | SQ | 4.8V             |
| RP130K491A  | SR | 4.9V             |
| RP130K501A  | SS | 5.0V             |
| RP131K511A  | SV | 5.1V             |
| RP131K521A  | SW | 5.2V             |
| RP131K531A  | SX | 5.3V             |
| RP131K121A5 | SU | 1.25V            |
| RP130K181A5 | RH | 1.85V            |
| RP130K281A5 | RU | 2.85V            |

RP130Kxx1B

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130K121B  | TA | 1.2V             |
| RP130K131B  | TB | 1.3V             |
| RP130K141B  | TC | 1.4V             |
| RP130K151B  | TD | 1.5V             |
| RP130K161B  | TE | 1.6V             |
| RP130K171B  | TF | 1.7V             |
| RP130K181B  | TG | 1.8V             |
| RP130K191B  | TJ | 1.9V             |
| RP130K201B  | TK | 2.0V             |
| RP130K211B  | TL | 2.1V             |
| RP130K221B  | TM | 2.2V             |
| RP130K231B  | TN | 2.3V             |
| RP130K241B  | TP | 2.4V             |
| RP130K251B  | TQ | 2.5V             |
| RP130K261B  | TR | 2.6V             |
| RP130K271B  | TS | 2.7V             |
| RP130K281B  | TT | 2.8V             |
| RP130K291B  | TV | 2.9V             |
| RP130K301B  | TW | 3.0V             |
| RP130K311B  | TX | 3.1V             |
| RP130K321B  | TY | 3.2V             |
| RP130K331B  | TZ | 3.3V             |
| RP130K341B  | UA | 3.4V             |
| RP130K351B  | UB | 3.5V             |
| RP130K361B  | UC | 3.6V             |
| RP130K371B  | UD | 3.7V             |
| RP130K381B  | UE | 3.8V             |
| RP130K391B  | UF | 3.9V             |
| RP130K401B  | UG | 4.0V             |
| RP130K411B  | UH | 4.1V             |
| RP130K421B  | UJ | 4.2V             |
| RP130K431B  | UK | 4.3V             |
| RP130K441B  | UL | 4.4V             |
| RP130K451B  | UM | 4.5V             |
| RP130K461B  | UN | 4.6V             |
| RP130K471B  | UP | 4.7V             |
| RP130K481B  | UQ | 4.8V             |
| RP130K491B  | UR | 4.9V             |
| RP130K501B  | US | 5.0V             |
| RP131K511B  | UV | 5.1V             |
| RP131K521B  | UW | 5.2V             |
| RP131K531B  | UX | 5.3V             |
| RP131K121B5 | UU | 1.25V            |
| RP130K181B5 | TH | 1.85V            |
| RP130K281B5 | TU | 2.85V            |

RP130Kxx1D

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130K121D  | VA | 1.2V             |
| RP130K131D  | VB | 1.3V             |
| RP130K141D  | VC | 1.4V             |
| RP130K151D  | VD | 1.5V             |
| RP130K161D  | VE | 1.6V             |
| RP130K171D  | VF | 1.7V             |
| RP130K181D  | VG | 1.8V             |
| RP130K191D  | VJ | 1.9V             |
| RP130K201D  | VK | 2.0V             |
| RP130K211D  | VL | 2.1V             |
| RP130K221D  | VM | 2.2V             |
| RP130K231D  | VN | 2.3V             |
| RP130K241D  | VP | 2.4V             |
| RP130K251D  | VQ | 2.5V             |
| RP130K261D  | VR | 2.6V             |
| RP130K271D  | VS | 2.7V             |
| RP130K281D  | VT | 2.8V             |
| RP130K291D  | VV | 2.9V             |
| RP130K301D  | VW | 3.0V             |
| RP130K311D  | VX | 3.1V             |
| RP130K321D  | VY | 3.2V             |
| RP130K331D  | VZ | 3.3V             |
| RP130K341D  | WA | 3.4V             |
| RP130K351D  | WB | 3.5V             |
| RP130K361D  | WC | 3.6V             |
| RP130K371D  | WD | 3.7V             |
| RP130K381D  | WE | 3.8V             |
| RP130K391D  | WF | 3.9V             |
| RP130K401D  | WG | 4.0V             |
| RP130K411D  | WH | 4.1V             |
| RP130K421D  | WJ | 4.2V             |
| RP130K431D  | WK | 4.3V             |
| RP130K441D  | WL | 4.4V             |
| RP130K451D  | WM | 4.5V             |
| RP130K461D  | WN | 4.6V             |
| RP130K471D  | WP | 4.7V             |
| RP130K481D  | WQ | 4.8V             |
| RP130K491D  | WR | 4.9V             |
| RP130K501D  | WS | 5.0V             |
| RP131K511D  | WV | 5.1V             |
| RP131K521D  | WW | 5.2V             |
| RP131K531D  | WX | 5.3V             |
| RP131K121D5 | WU | 1.25V            |
| RP130K181D5 | VH | 1.85V            |
| RP130K281D5 | VU | 2.85V            |

# • Power Dissipation (SC-82AB)

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:



## Measurement Conditions

|                  | Standard Land Pattern                         |
|------------------|-----------------------------------------------|
| Environment      | Mounting on Board (Wind velocity=0m/s)        |
| Board Material   | Glass cloth epoxy plastic (Double Layers)     |
| Board Dimensions | 40mm x 40mm x 1.6mm                           |
| Copper Ratio     | Top side: Approx. 50%, Back side: Approx. 50% |
| Through-hole     | $\phi 0.5\text{mm}$ x 44pcs                   |

## Measurement Result

( $T_a=25^\circ\text{C}$ )

|                    | Standard Land Pattern                                                                          | Free Air                                      |
|--------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Power Dissipation  | 380mW ( $T_{j\text{max}}=125^\circ\text{C}$ )<br>475mW ( $T_{j\text{max}}=150^\circ\text{C}$ ) | 150mW ( $T_{j\text{max}}=125^\circ\text{C}$ ) |
| Thermal Resistance | $\theta_{ja}=(125-25^\circ\text{C})/0.38\text{W}=263^\circ\text{C/W}$                          | $667^\circ\text{C/W}$                         |



Measurement Board Pattern

○ IC Mount Area (Unit : mm)


The above graph shows the Power Dissipation of the package based on  $T_{j\text{max}}=125^\circ\text{C}$  and  $T_{j\text{max}}=150^\circ\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime. Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

|                |                                               |
|----------------|-----------------------------------------------|
| Operating Time | Estimated years<br>(Operating four hours/day) |
| 13,000 hours   | 9years                                        |

## RP130x


NO.EA-173-131031

### • Package Dimensions (SC-82AB)



### • Mark Specifications (SC-82AB)

- ①②: Product Code ... Please refer to RP130Q Series Mark Specification Table
- ③④: Lot Number ... Alphanumeric Serial Number



**• RP130Q Series Mark Specification Table (SC-82AB)**
**RP130Qxx1A**

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130Q121A  | AA | 1.2V             |
| RP130Q131A  | AB | 1.3V             |
| RP130Q141A  | AC | 1.4V             |
| RP130Q151A  | AD | 1.5V             |
| RP130Q161A  | AE | 1.6V             |
| RP130Q171A  | AF | 1.7V             |
| RP130Q181A  | AG | 1.8V             |
| RP130Q191A  | AJ | 1.9V             |
| RP130Q201A  | AK | 2.0V             |
| RP130Q211A  | BA | 2.1V             |
| RP130Q221A  | BB | 2.2V             |
| RP130Q231A  | BC | 2.3V             |
| RP130Q241A  | BD | 2.4V             |
| RP130Q251A  | BE | 2.5V             |
| RP130Q261A  | BF | 2.6V             |
| RP130Q271A  | BG | 2.7V             |
| RP130Q281A  | BH | 2.8V             |
| RP130Q291A  | BK | 2.9V             |
| RP130Q301A  | CA | 3.0V             |
| RP130Q311A  | CB | 3.1V             |
| RP130Q321A  | CC | 3.2V             |
| RP130Q331A  | CD | 3.3V             |
| RP130Q341A  | CE | 3.4V             |
| RP130Q351A  | CF | 3.5V             |
| RP130Q361A  | CG | 3.6V             |
| RP130Q371A  | CH | 3.7V             |
| RP130Q381A  | CJ | 3.8V             |
| RP130Q391A  | CK | 3.9V             |
| RP130Q401A  | DA | 4.0V             |
| RP130Q411A  | DB | 4.1V             |
| RP130Q421A  | DC | 4.2V             |
| RP130Q431A  | DD | 4.3V             |
| RP130Q441A  | DE | 4.4V             |
| RP130Q451A  | DF | 4.5V             |
| RP130Q461A  | DG | 4.6V             |
| RP130Q471A  | DH | 4.7V             |
| RP130Q481A  | DJ | 4.8V             |
| RP130Q491A  | DK | 4.9V             |
| RP130Q501A  | EA | 5.0V             |
| RP130Q511A  | ED | 5.1V             |
| RP130Q521A  | EE | 5.2V             |
| RP130Q531A  | EF | 5.3V             |
| RP130Q121A5 | EC | 1.25V            |
| RP130Q181A5 | AH | 1.85V            |
| RP130Q281A5 | BJ | 2.85V            |

**RP130Qxx1B**

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130Q121B  | FA | 1.2V             |
| RP130Q131B  | FB | 1.3V             |
| RP130Q141B  | FC | 1.4V             |
| RP130Q151B  | FD | 1.5V             |
| RP130Q161B  | FE | 1.6V             |
| RP130Q171B  | FF | 1.7V             |
| RP130Q181B  | FG | 1.8V             |
| RP130Q191B  | FJ | 1.9V             |
| RP130Q201B  | FK | 2.0V             |
| RP130Q211B  | GA | 2.1V             |
| RP130Q221B  | GB | 2.2V             |
| RP130Q231B  | GC | 2.3V             |
| RP130Q241B  | GD | 2.4V             |
| RP130Q251B  | GE | 2.5V             |
| RP130Q261B  | GF | 2.6V             |
| RP130Q271B  | GG | 2.7V             |
| RP130Q281B  | GH | 2.8V             |
| RP130Q291B  | GK | 2.9V             |
| RP130Q301B  | HA | 3.0V             |
| RP130Q311B  | HB | 3.1V             |
| RP130Q321B  | HC | 3.2V             |
| RP130Q331B  | HD | 3.3V             |
| RP130Q341B  | HE | 3.4V             |
| RP130Q351B  | HF | 3.5V             |
| RP130Q361B  | HG | 3.6V             |
| RP130Q371B  | HH | 3.7V             |
| RP130Q381B  | HJ | 3.8V             |
| RP130Q391B  | HK | 3.9V             |
| RP130Q401B  | JA | 4.0V             |
| RP130Q411B  | JB | 4.1V             |
| RP130Q421B  | JC | 4.2V             |
| RP130Q431B  | JD | 4.3V             |
| RP130Q441B  | JE | 4.4V             |
| RP130Q451B  | JF | 4.5V             |
| RP130Q461B  | JG | 4.6V             |
| RP130Q471B  | JH | 4.7V             |
| RP130Q481B  | JJ | 4.8V             |
| RP130Q491B  | JK | 4.9V             |
| RP130Q501B  | KA | 5.0V             |
| RP130Q511B  | KD | 5.1V             |
| RP130Q521B  | KE | 5.2V             |
| RP130Q531B  | KF | 5.3V             |
| RP130Q121B5 | KC | 1.25V            |
| RP130Q181B5 | FH | 1.85V            |
| RP130Q281B5 | GJ | 2.85V            |

**RP130Qxx1D**

| Part Number | ①② | V <sub>SET</sub> |
|-------------|----|------------------|
| RP130Q121D  | LA | 1.2V             |
| RP130Q131D  | LB | 1.3V             |
| RP130Q141D  | LC | 1.4V             |
| RP130Q151D  | LD | 1.5V             |
| RP130Q161D  | LE | 1.6V             |
| RP130Q171D  | LF | 1.7V             |
| RP130Q181D  | LG | 1.8V             |
| RP130Q191D  | LJ | 1.9V             |
| RP130Q201D  | LK | 2.0V             |
| RP130Q211D  | MA | 2.1V             |
| RP130Q221D  | MB | 2.2V             |
| RP130Q231D  | MC | 2.3V             |
| RP130Q241D  | MD | 2.4V             |
| RP130Q251D  | ME | 2.5V             |
| RP130Q261D  | MF | 2.6V             |
| RP130Q271D  | MG | 2.7V             |
| RP130Q281D  | MH | 2.8V             |
| RP130Q291D  | MK | 2.9V             |
| RP130Q301D  | NA | 3.0V             |
| RP130Q311D  | NB | 3.1V             |
| RP130Q321D  | NC | 3.2V             |
| RP130Q331D  | ND | 3.3V             |
| RP130Q341D  | NE | 3.4V             |
| RP130Q351D  | NF | 3.5V             |
| RP130Q361D  | NG | 3.6V             |
| RP130Q371D  | NH | 3.7V             |
| RP130Q381D  | NJ | 3.8V             |
| RP130Q391D  | NK | 3.9V             |
| RP130Q401D  | PA | 4.0V             |
| RP130Q411D  | PB | 4.1V             |
| RP130Q421D  | PC | 4.2V             |
| RP130Q431D  | PD | 4.3V             |
| RP130Q441D  | PE | 4.4V             |
| RP130Q451D  | PF | 4.5V             |
| RP130Q461D  | PG | 4.6V             |
| RP130Q471D  | PH | 4.7V             |
| RP130Q481D  | PJ | 4.8V             |
| RP130Q491D  | PK | 4.9V             |
| RP130Q501D  | QA | 5.0V             |
| RP130Q511D  | QD | 5.1V             |
| RP130Q521D  | QE | 5.2V             |
| RP130Q531D  | QF | 5.3V             |
| RP130Q121D5 | QC | 1.25V            |
| RP130Q181D5 | LH | 1.85V            |
| RP130Q281D5 | MJ | 2.85V            |

# • Power Dissipation (SOT-23-5)

Power Dissipation ( $P_D$ ) depends on conditions of mounting on board. This specification is based on the measurement at the condition below:

(Power Dissipation (SOT-23-5) is substitution of SOT-23-6.)


## Measurement Conditions

|                  | Standard Test Land Pattern                    |
|------------------|-----------------------------------------------|
| Environment      | Mounting on Board (Wind velocity=0m/s)        |
| Board Material   | Glass cloth epoxy plastic (Double sided)      |
| Board Dimensions | 40mm x 40mm x 1.6mm                           |
| Copper Ratio     | Top side: Approx. 50%, Back side: Approx. 50% |
| Through-holes    | $\phi$ 0.5mm x 44pcs                          |


## Measurement Result

( $T_a=25^\circ\text{C}$ ,  $T_{j\text{max}}=125^\circ\text{C}$ )

|                    | Standard Land Pattern                                                                        | Free Air              |
|--------------------|----------------------------------------------------------------------------------------------|-----------------------|
| Power Dissipation  | 420mW( $T_{j\text{max}}=125^\circ\text{C}$ )<br>525mW( $T_{j\text{max}}=150^\circ\text{C}$ ) | 250mW                 |
| Thermal Resistance | $\theta_{ja} = (125-25^\circ\text{C})/0.42\text{W} = 238^\circ\text{C/W}$                    | $400^\circ\text{C/W}$ |



Power Dissipation



Measurement Board Pattern

○ IC Mount Area (Unit: mm)

The above graph shows the Power Dissipation of the package based on  $T_{j\text{max}}=125^\circ\text{C}$  and  $T_{j\text{max}}=150^\circ\text{C}$ . Operating the IC in the shaded area in the graph might have an influence it's lifetime.

Operating time must be within the time limit described in the table below, in case of operating in the shaded area.

| Operating Time | Estimated years<br>(Operating four hours/day) |
|----------------|-----------------------------------------------|
| 9,000 hours    | 6years                                        |



**RP130x**

NO.EA-173-131031

● **RP130N Series Mark Specification Table (SOT-23-5)****RP130Nxx1A**

| Part Number | ①②③ | V <sub>SET</sub> |
|-------------|-----|------------------|
| RP130N121A  | H0A | 1.2V             |
| RP130N131A  | H0B | 1.3V             |
| RP130N141A  | H0C | 1.4V             |
| RP130N151A  | H0D | 1.5V             |
| RP130N161A  | H0E | 1.6V             |
| RP130N171A  | H0F | 1.7V             |
| RP130N181A  | H0G | 1.8V             |
| RP130N191A  | H0J | 1.9V             |
| RP130N201A  | H0K | 2.0V             |
| RP130N211A  | H0L | 2.1V             |
| RP130N221A  | H0M | 2.2V             |
| RP130N231A  | H0N | 2.3V             |
| RP130N241A  | H0P | 2.4V             |
| RP130N251A  | H0Q | 2.5V             |
| RP130N261A  | H0R | 2.6V             |
| RP130N271A  | H0S | 2.7V             |
| RP130N281A  | H0T | 2.8V             |
| RP130N291A  | H0V | 2.9V             |
| RP130N301A  | H0W | 3.0V             |
| RP130N311A  | H0X | 3.1V             |
| RP130N321A  | H0Y | 3.2V             |
| RP130N331A  | H0Z | 3.3V             |
| RP130N341A  | J0A | 3.4V             |
| RP130N351A  | J0B | 3.5V             |
| RP130N361A  | J0C | 3.6V             |
| RP130N371A  | J0D | 3.7V             |
| RP130N381A  | J0E | 3.8V             |
| RP130N391A  | J0F | 3.9V             |
| RP130N401A  | J0G | 4.0V             |
| RP130N411A  | J0H | 4.1V             |
| RP130N421A  | J0J | 4.2V             |
| RP130N431A  | J0K | 4.3V             |
| RP130N441A  | J0L | 4.4V             |
| RP130N451A  | J0M | 4.5V             |
| RP130N461A  | J0N | 4.6V             |
| RP130N471A  | J0P | 4.7V             |
| RP130N481A  | J0Q | 4.8V             |
| RP130N491A  | J0R | 4.9V             |
| RP130N501A  | J0S | 5.0V             |
| RP130N511A  | J0V | 5.1V             |
| RP130N521A  | J0W | 5.2V             |
| RP130N531A  | J0X | 5.3V             |
| RP130N121A5 | J0U | 1.25V            |
| RP130N181A5 | H0H | 1.85V            |
| RP130N281A5 | H0U | 2.85V            |


**RP130Nxx1B**

| Part Number | ①②③ | V <sub>SET</sub> |
|-------------|-----|------------------|
| RP130N121B  | H1A | 1.2V             |
| RP130N131B  | H1B | 1.3V             |
| RP130N141B  | H1C | 1.4V             |
| RP130N151B  | H1D | 1.5V             |
| RP130N161B  | H1E | 1.6V             |
| RP130N171B  | H1F | 1.7V             |
| RP130N181B  | H1G | 1.8V             |
| RP130N191B  | H1J | 1.9V             |
| RP130N201B  | H1K | 2.0V             |
| RP130N211B  | H1L | 2.1V             |
| RP130N221B  | H1M | 2.2V             |
| RP130N231B  | H1N | 2.3V             |
| RP130N241B  | H1P | 2.4V             |
| RP130N251B  | H1Q | 2.5V             |
| RP130N261B  | H1R | 2.6V             |
| RP130N271B  | H1S | 2.7V             |
| RP130N281B  | H1T | 2.8V             |
| RP130N291B  | H1V | 2.9V             |
| RP130N301B  | H1W | 3.0V             |
| RP130N311B  | H1X | 3.1V             |
| RP130N321B  | H1Y | 3.2V             |
| RP130N331B  | H1Z | 3.3V             |
| RP130N341B  | J1A | 3.4V             |
| RP130N351B  | J1B | 3.5V             |
| RP130N361B  | J1C | 3.6V             |
| RP130N371B  | J1D | 3.7V             |
| RP130N381B  | J1E | 3.8V             |
| RP130N391B  | J1F | 3.9V             |
| RP130N401B  | J1G | 4.0V             |
| RP130N411B  | J1H | 4.1V             |
| RP130N421B  | J1J | 4.2V             |
| RP130N431B  | J1K | 4.3V             |
| RP130N441B  | J1L | 4.4V             |
| RP130N451B  | J1M | 4.5V             |
| RP130N461B  | J1N | 4.6V             |
| RP130N471B  | J1P | 4.7V             |
| RP130N481B  | J1Q | 4.8V             |
| RP130N491B  | J1R | 4.9V             |
| RP130N501B  | J1S | 5.0V             |
| RP130N511B  | J1V | 5.1V             |
| RP130N521B  | J1W | 5.2V             |
| RP130N531B  | J1X | 5.3V             |
| RP130N121B5 | J1U | 1.25V            |
| RP130N181B5 | H1H | 1.85V            |
| RP130N281B5 | H1U | 2.85V            |


**RP130Nxx1D**

| Part Number | ①②③ | V <sub>SET</sub> |
|-------------|-----|------------------|
| RP130N121D  | H2A | 1.2V             |
| RP130N131D  | H2B | 1.3V             |
| RP130N141D  | H2C | 1.4V             |
| RP130N151D  | H2D | 1.5V             |
| RP130N161D  | H2E | 1.6V             |
| RP130N171D  | H2F | 1.7V             |
| RP130N181D  | H2G | 1.8V             |
| RP130N191D  | H2J | 1.9V             |
| RP130N201D  | H2K | 2.0V             |
| RP130N211D  | H2L | 2.1V             |
| RP130N221D  | H2M | 2.2V             |
| RP130N231D  | H2N | 2.3V             |
| RP130N241D  | H2P | 2.4V             |
| RP130N251D  | H2Q | 2.5V             |
| RP130N261D  | H2R | 2.6V             |
| RP130N271D  | H2S | 2.7V             |
| RP130N281D  | H2T | 2.8V             |
| RP130N291D  | H2V | 2.9V             |
| RP130N301D  | H2W | 3.0V             |
| RP130N311D  | H2X | 3.1V             |
| RP130N321D  | H2Y | 3.2V             |
| RP130N331D  | H2Z | 3.3V             |
| RP130N341D  | J2A | 3.4V             |
| RP130N351D  | J2B | 3.5V             |
| RP130N361D  | J2C | 3.6V             |
| RP130N371D  | J2D | 3.7V             |
| RP130N381D  | J2E | 3.8V             |
| RP130N391D  | J2F | 3.9V             |
| RP130N401D  | J2G | 4.0V             |
| RP130N411D  | J2H | 4.1V             |
| RP130N421D  | J2J | 4.2V             |
| RP130N431D  | J2K | 4.3V             |
| RP130N441D  | J2L | 4.4V             |
| RP130N451D  | J2M | 4.5V             |
| RP130N461D  | J2N | 4.6V             |
| RP130N471D  | J2P | 4.7V             |
| RP130N481D  | J2Q | 4.8V             |
| RP130N491D  | J2R | 4.9V             |
| RP130N501D  | J2S | 5.0V             |
| RP130N511D  | J2V | 5.1V             |
| RP130N521D  | J2W | 5.2V             |
| RP130N531D  | J2X | 5.3V             |
| RP130N121D5 | J2U | 1.25V            |
| RP130N181D5 | H2H | 1.85V            |
| RP130N281D5 | H2U | 2.85V            |


## TEST CIRCUITS




**Basic Test Circuit**



**Supply Current Test Circuit**






**Ripple Rejection Test Circuit**





**Load Transient Response Test Circuit**


## TYPICAL CHARACTERISTICS

### 1) Output Voltage vs. Output Current ( $C_1=0.47\mu\text{F}$ , $C_2=0.47\mu\text{F}$ , $T_{\text{opt}}=25^\circ\text{C}$ )






### 2) Output Voltage vs. Input Voltage ( $C_1=0.47\mu\text{F}$ , $C_2=0.47\mu\text{F}$ , $T_{\text{opt}}=25^\circ\text{C}$ )










### 3) Supply Current vs. Input Voltage ( $C1=0.47\mu\text{F}$ , $C2=0.47\mu\text{F}$ , $T_{opt}=25^{\circ}\text{C}$ )




4) Output Voltage vs. Temperature ( $I_{OUT}=1mA$ ,  $C1=0.47\mu F$ ,  $C2=0.47\mu F$ )



5) Supply Current vs. Temperature ( $I_{OUT}=0mA$ ,  $C1=0.47\mu F$ ,  $C2=0.47\mu F$ )




RP130x501x




# 6) Dropout Voltage vs. Output Current ( $C1=0.47\mu F$ , $C2=0.47\mu F$ )


RP130x121x




RP130x281x





RP130x501x





## 7) Dropout Voltage vs. Set Output Voltage (C1=0.47μF, C2=0.47μF)




## 8) Ripple Rejection vs. Input Bias Voltage (C1=none, C2=0.47μF, Ripple=0.2V<sub>p-p</sub>, T<sub>opt</sub>=25°C)






## 9) Ripple Rejection vs. Frequency (C1=none, C2=0.47μF, Ripple=0.2V<sub>p-p</sub>, T<sub>opt</sub>=25°C)








**10) Input Transient Response ( $I_{OUT}=30mA$ ,  $t_r=t_f=5\mu s$ ,  $C1=none$ ,  $C2=0.47\mu F$ ,  $T_{opt}=25^\circ C$ )**





## RP130x


NO.EA-173-131031

### 11) Load Transient Response ( $t_r=t_f=0.5\mu s$ , $C_1=0.47\mu F$ , $C_2=0.47\mu F$ , $I_{OUT}=50mA \leftrightarrow 100mA$ , $T_{opt}=25^\circ C$ )












### 12) Load Transient Response ( $t_r=t_f=0.5\mu s$ , $C_1=0.47\mu F$ , $C_2=0.47\mu F$ , $I_{OUT}=1mA \leftrightarrow 150mA$ , $T_{opt}=25^\circ C$ )














### 13) Turn On Speed with CE pin ( $C_1=0.47\mu$ F, $C_2=0.47\mu$ F, $T_{opt}=25^\circ$ C)






14) Turn Off Speed with CE pin (D Version) ( $C_1=0.47\mu\text{F}$ ,  $C_2=0.47\mu\text{F}$ ,  $T_{\text{opt}}=25^\circ\text{C}$ )





### 15) Minimum Operating Voltage ( $C1=0.47\mu\text{F}$ , $C2=0.47\mu\text{F}$ )



Hatched area is available  
for 1.2V output.

## ESR vs. Output Current

When using these ICs, consider the following points:

The relations between  $I_{OUT}$  (Output Current) and ESR of an output capacitor are shown below.




The conditions when the white noise level is under  $40\mu\text{V}$  (Avg.) are marked as the hatched area in the graph.

### Measurement conditions

Frequency Band : 10Hz to 3MHz

Temperature :  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$

C1, C2 :  $0.47\mu\text{F}$





1. The products and the product specifications described in this document are subject to change or discontinuation of production without notice for reasons such as improvement. Therefore, before deciding to use the products, please refer to Ricoh sales representatives for the latest information thereon.
2. The materials in this document may not be copied or otherwise reproduced in whole or in part without prior written consent of Ricoh.
3. Please be sure to take any necessary formalities under relevant laws or regulations before exporting or otherwise taking out of your country the products or the technical information described herein.
4. The technical information described in this document shows typical characteristics of and example application circuits for the products. The release of such information is not to be construed as a warranty of or a grant of license under Ricoh's or any third party's intellectual property rights or any other rights.
5. The products listed in this document are intended and designed for use as general electronic components in standard applications (office equipment, telecommunication equipment, measuring instruments, consumer electronic products, amusement equipment etc.). Those customers intending to use a product in an application requiring extreme quality and reliability, for example, in a highly specific application where the failure or misoperation of the product could result in human injury or death (aircraft, spacevehicle, nuclear reactor control system, traffic control system, automotive and transportation equipment, combustion equipment, safety devices, life support system etc.) should first contact us.
6. We are making our continuous effort to improve the quality and reliability of our products, but semiconductor products are likely to fail with certain probability. In order to prevent any injury to persons or damages to property resulting from such failure, customers should be careful enough to incorporate safety measures in their design, such as redundancy feature, fire containment feature and fail-safe feature. We do not assume any liability or responsibility for any loss or damage arising from misuse or inappropriate use of the products.
7. Anti-radiation design is not implemented in the products described in this document.
8. Please contact Ricoh sales representatives should you have any questions or comments concerning the products or the technical information.



**Ricoh is committed to reducing the environmental loading materials in electrical devices with a view to contributing to the protection of human health and the environment.**

Ricoh has been providing RoHS compliant products since April 1, 2006 and Halogen-free products since April 1, 2012.

**RICOH** RICOH ELECTRONIC DEVICES CO., LTD.

<http://www.e-devices.ricoh.co.jp/en/>

#### Sales & Support Offices

##### **RICOH ELECTRONIC DEVICES CO., LTD.**

##### **Higashi-Shinagawa Office (International Sales)**

3-32-3, Higashi-Shinagawa, Shinagawa-ku, Tokyo 140-8655, Japan  
Phone: +81-3-5479-2857 Fax: +81-3-5479-0502

##### **RICOH EUROPE (NETHERLANDS) B.V.**

##### **Semiconductor Support Centre**

Prof. W.H. Keesomlaan 1, 1183 DJ Amstelveen, The Netherlands  
Phone: +31-20-5474-309

##### **RICOH ELECTRONIC DEVICES KOREA CO., LTD.**

3F, Haesung Bldg. 504, Teheran-ro, Gangnam-gu, Seoul, 135-725, Korea  
Phone: +82-2-2135-5700 Fax: +82-2-2051-5713

##### **RICOH ELECTRONIC DEVICES SHANGHAI CO., LTD.**

Room 403, No.2 Building, No.690 Bilbo Road, Pu Dong New District, Shanghai 201203,  
People's Republic of China  
Phone: +86-21-5027-3200 Fax: +86-21-5027-3299

##### **RICOH ELECTRONIC DEVICES CO., LTD.**

##### **Taipei office**

Room 109, 10F-1, No.51, Hengyang Rd., Taipei City, Taiwan (R.O.C.)  
Phone: +886-2-2313-1621/1622 Fax: +886-2-2313-1623