

2N7002E

N-channel TrenchMOS FET

Rev. 03 — 28 April 2006 Product data sheet

1. Product profile

1.1 General description

N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology.

1.2 Features

- Logic level threshold compatible
- Surface-mounted package
- Very fast switching
- TrenchMOS technology

1.3 Applications



- Logic level translator
- High-speed line driver

1.4 Quick reference data

- $V_{DS} \leq 60$ V
- $R_{DSon} \leq 3\ \Omega$
- $I_D \leq 385$ mA
- $P_{tot} \leq 0.83$ W

2. Pinning information

Table 1: Pinning

Pin	Description	Simplified outline	Symbol
1	gate (G)	 SOT23	
2	source (S)		
3	drain (D)		

PHILIPS

3. Ordering information

Table 2: Ordering information

Type number	Package		
	Name	Description	Version
2N7002E	TO-236AB	plastic surface-mounted package; 3 leads	SOT23


4. Limiting values

Table 3: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).


Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage	25 °C ≤ T_j ≤ 150 °C	-	60	V
V_{DGR}	drain-gate voltage (DC)	25 °C ≤ T_j ≤ 150 °C; R_{GS} = 20 kΩ	-	60	V
V_{GS}	gate-source voltage		-	±30	V
V_{GSM}	peak gate-source voltage	t_p ≤ 50 µs; pulsed; duty cycle = 25 %	-	±40	V
I_D	drain current	T_{sp} = 25 °C; V_{GS} = 10 V; see Figure 2 and 3	-	385	mA
		T_{sp} = 100 °C; V_{GS} = 10 V; see Figure 2	-	245	mA
I_{DM}	peak drain current	T_{sp} = 25 °C; pulsed; t_p ≤ 10 µs; see Figure 3	-	1.5	A
P_{tot}	total power dissipation	T_{sp} = 25 °C; see Figure 1	-	0.83	W
T_{stg}	storage temperature		–65	+150	°C
T_j	junction temperature		–65	+150	°C
Source-drain diode					
I_S	source current	T_{sp} = 25 °C	-	385	mA
I_{SM}	peak source current	T_{sp} = 25 °C; pulsed; t_p ≤ 10 µs	-	1.5	mA

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.




$$P_{der} = \frac{P_{tot}}{P_{tot(25\ ^\circ C)}} \times 100\ \%$$

Fig 1. Normalized total power dissipation as a function of solder point temperature



$$I_{der} = \frac{I_D}{I_{D(25\ ^\circ C)}} \times 100\ \%$$

Fig 2. Normalized continuous drain current as a function of solder point temperature



T_{sp} = 25 °C; I_{DM} is single pulse

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.

5. Thermal characteristics

Table 4: Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point	see Figure 4		-	-	150	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient		[1]	-	-	350	K/W

[1] Mounted on a printed-circuit board; minimum footprint; vertical in still air




Fig 4. Transient thermal impedance from junction to solder point as a function of pulse duration

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.


6. Characteristics

Table 5: Characteristics

T_j = 25 °C unless otherwise specified.


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = 10 µA; V_{GS} = 0 V				
		T_j = 25 °C	60	-	-	V
		T_j = −55 °C	55	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	I_D = 0.25 mA; V_{DS} = V_{GS}; see Figure 9 and 10				
		T_j = 25 °C	1	2	2.5	V
		T_j = 150 °C	0.6	-	-	V
		T_j = −55 °C	-	-	2.75	V
I_{DSS}	drain leakage current	V_{DS} = 48 V; V_{GS} = 0 V				
		T_j = 25 °C	-	-	1	µA
		T_j = 150 °C	-	-	10	µA
I_{GSS}	gate leakage current	V_{GS} = ±15 V; V_{DS} = 0 V	-	10	100	nA
R_{DSon}	drain-source on-state resistance	V_{GS} = 10 V; I_D = 500 mA; see Figure 6 and 8				
		T_j = 25 °C	-	0.78	3	Ω
		T_j = 150 °C	-	1.45	5.5	Ω
		V_{GS} = 4.5 V; I_D = 75 mA; see Figure 6 and 8	-	1.2	4	Ω
Dynamic characteristics						
$Q_{G(tot)}$	total gate charge	I_D = 300 mA; V_{DS} = 30 V; V_{GS} = 10 V; see Figure 11 and 12	-	0.69	-	nC
Q_{GS}	gate-source charge		-	0.1	-	nC
Q_{GD}	gate-drain charge		-	0.27	-	nC
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = 10 V; f = 1 MHz; see Figure 14	-	31	50	pF
C_{oss}	output capacitance		-	6.8	30	pF
C_{rss}	reverse transfer capacitance		-	3.5	10	pF
t_{on}	turn-on time	V_{DS} = 50 V; R_L = 250 Ω; V_{GS} = 10 V; R_G = 50 Ω; R_{GS} = 50 Ω	-	2.5	10	ns
t_{off}	turn-off time		-	11	15	ns
Source-drain diode						
V_{SD}	source-drain voltage	I_S = 300 mA; V_{GS} = 0 V; see Figure 13	-	0.85	1.5	V
t_{rr}	reverse recovery time	I_S = 300 mA; dI_S/dt = −100 A/µs; V_{GS} = 0 V	-	30	-	ns
Q_r	recovered charge		-	30	-	nC

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.




T_j = 25 °C

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values




T_j = 25 °C

Fig 6. Drain-source on-state resistance as a function of drain current; typical values



T_j = 25 °C and 150 °C; $V_{DS} > I_D \times R_{DSon}$


Fig 7. Transfer characteristics: drain current as a function of gate-source voltage; typical values



$$a = \frac{R_{DSon}}{R_{DSon(25\ ^\circ C)}}$$


Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.




I_D = 0.25 mA; V_{DS} = V_{GS}

Fig 9. Gate-source threshold voltage as a function of junction temperature



T_j = 25 °C; V_{DS} = 5 V

Fig 10. Sub-threshold drain current as a function of gate-source voltage



I_D = 0.3 A; V_{DS} = 30 V

Fig 11. Gate-source voltage as a function of gate charge; typical values






Fig 12. Gate charge waveform definitions

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.



T_j = 25 °C and 150 °C; V_{GS} = 0 V

Fig 13. Source current as a function of source-drain voltage; typical values




V_{GS} = 0 V; f = 1 MHz

Fig 14. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.

7. Package outline

Plastic surface-mounted package; 3 leads **SOT23**



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1 max.	b_p	c	D	E	e	e_1	H_E	L_p	Q	v	w
mm	1.1 0.9	0.1	0.48 0.38	0.15 0.09	3.0 2.8	1.4 1.2	1.9	0.95	2.5 2.1	0.45 0.15	0.55 0.45	0.2	0.1

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT23		TO-236AB				~~04-11-04~~ 06-03-16

Fig 15. Package outline SOT23

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.

8. Revision history

Table 6: Revision history

Document ID	Release date	Data sheet status	Change notice	Doc. number	Supersedes
2N7002E_3	20060428	Product data sheet	-	-	2N7002E_2
Modifications:	• Table 5 “Characteristics”: $V_{GS(th)}$ I_D condition modified • Table 5 “Characteristics”: $V_{GS(th)}$ maximum limits modified • Table 5 “Characteristics”: R_{DSon} typical values modified • Table 5 “Characteristics”: g_{fs} removed • Table 5 “Characteristics”: Addition of $Q_{G(tot)}$, Q_{GS} and Q_{GD} • Table 5 “Characteristics”: C_{iss}, C_{oss} and C_{rss} values modified • Table 5 “Characteristics”: t_{on} and t_{off} typical values modified • Figure 3, 4, 5, 6, 7, 9, 10, 13 and 14: modified • Figure 11: added				
2N7002E_2	20050426	Product data sheet	-	9397 750 14944	2N7002E-01
2N7002E-01	20020211	Product data	-	9397 750 09095	-

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.

9. Data sheet status

Level	Data sheet status [1]	Product status [2] [3]	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

Notice — All referenced brands, product names, service names and trademarks are the property of their respective owners.
TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

13. Contact information

For additional information, please visit: **http://www.semiconductors.philips.com**

For sales office addresses, send an email to: **sales.addresses@www.semiconductors.philips.com**

© Koninklijke Philips Electronics N.V. 2006. All rights reserved.