
TOSHIBA CMOS DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TC7W08F, TC7W08FU, TC7W08FK

DUAL 2-INPUT AND GATE


The TC7W08 is a high speed C^2MOS 2-INPUT AND GATE fabricated with silicon gate C^2MOS technology.
It achives the high speed operation similar to equivalent LSTTL while maintaining the C^2MOS low power dissipation.
The internal circuit is composed of 3 stages including buffer output, which enables high noise immunity and stable output.
All inputs are equipped with protection circuits against static discharge or transient excess voltage.

TC7W08F




SOP8-P-1.27

TC7W08FU



SSOP8-P-0.65

TC7W08FK




SSOP8-P-0.50A

FEATURES

- High Speed ..... t_{pd} = 6ns (Typ.) at V_{CC} = 5V
- Low Power Dissipation ..... I_{CC} = 1μA (Max.) at Ta = 25°C
- High Noise Immunity ..... $V_{NIH} = V_{NIL}$ = 28% V_{CC} (Min.)
- Output Drive Capability ..... 10 LSTTL Loads
- Symmetrical Output Impedance ... $|I_{OH}| = I_{OL}$ = 4mA (Min.)
- Balanced Propagation Delays ..... $t_{pLH} \fallingdotseq t_{pHL}$
- Wide Operating Voltage Range ... $V_{CC\,(opr)}$ = 2~6V

MARKING



Weight
SOP8-P-1.27 : 0.05g (Typ.)
SSOP8-P-0.65 : 0.02g (Typ.)
SSOP8-P-0.50A : 0.01g (Typ.)


980910EBA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage Range	V_{CC}	−0.5~7	V
DC Input Voltage	V_{IN}	−0.5~V_{CC}+0.5	V
DC Output Voltage	V_{OUT}	−0.5~V_{CC}+0.5	V
Input Diode Current	I_{IK}	±20	mA
Output Diode Current	I_{OK}	±20	mA
DC Output Current	I_{OUT}	±25	mA
DC V_{CC} / Ground Current	I_{CC}	±25	mA
Power Dissipation	P_D	300 (FM8, SM8)	mW
		200 (US8)	
Storage Temperature	T_{stg}	−65~150	°C
Lead Temperature (10s)	T_L	260	°C


LOGIC DIAGRAM



TRUTH TABLE

A	B	Y
L	L	L
L	H	L
H	L	L
H	H	H

PIN ASSIGNMENT (TOP VIEW)



RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V_{CC}	2~6	V
Input Voltage	V_{IN}	0~V_{CC}	V
Output Voltage	V_{OUT}	0~V_{CC}	V
Operating Temperature	T_{opr}	−40~85	°C
Input Rise and Fall Time	t_r, t_f	0~1000 (V_{CC} = 2.0V) 0~ 500 (V_{CC} = 4.5V) 0~ 400 (V_{CC} = 6.0V)	ns

DC ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	TEST CONDITION		V_{CC}	Ta = 25°C MIN.	Ta = 25°C TYP.	Ta = 25°C MAX.	Ta = −40~85°C MIN.	Ta = −40~85°C MAX.	UNIT
High-Level Input Voltage	V_{IH}	—		2.0	1.5	—	—	1.5	—	V
				4.5	3.15	—	—	3.15	—	
				6.0	4.2	—	—	4.2	—	
Low-Level Input Voltage	V_{IL}	—		2.0	—	—	0.5	—	0.5	V
				4.5	—	—	1.35	—	1.35	
				6.0	—	—	1.8	—	1.8	
High-Level Output Voltage	V_{OH}	$V_{IN} = V_{IH}$	$I_{OH} = -20\mu A$	2.0	1.9	2.0	—	1.9	—	V
				4.5	4.4	4.5	—	4.4	—	
				6.0	5.9	6.0	—	5.9	—	
			$I_{OH} = -4mA$	4.5	4.18	4.31	—	4.13	—	
			$I_{OH} = -5.2mA$	6.0	5.68	5.80	—	5.63	—	
Low-Level Output Voltage	V_{OL}	$V_{IN} = V_{IH}$ or V_{IL}	$I_{OL} = 20\mu A$	2.0	—	0.0	0.1	—	0.1	V
				4.5	—	0.0	0.1	—	0.1	
				6.0	—	0.0	0.1	—	0.1	
			$I_{OL} = 4mA$	4.5	—	0.17	0.26	—	0.33	
			$I_{OL} = 5.2mA$	6.0	—	0.18	0.26	—	0.33	
Input Leakage Current	I_{IN}	$V_{IN} = V_{CC}$ or GND		6.0	—	—	±0.1	—	±1.0	μA
Quiescent Supply Current	I_{CC}	$V_{IN} = V_{CC}$ or GND		6.0	—	—	1.0	—	10.0	

AC ELECTRICAL CHARACTERISTICS (C_L = 15pF, V_{CC} = 5V, Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	Ta = 25°C			UNIT
			MIN.	TYP.	MAX.	
Output Transition Time	t_{TLH} t_{THL}	—	—	4	8	ns
Propagation Delay Time	t_{pLH} t_{pHL}	—	—	6	12	ns

AC ELECTRICAL CHARACTERISTICS (C_L = 50pF, Input $t_r = t_f$ = 6ns)

CHARACTERISTIC	SYMBOL	TEST CONDITION	V_{CC}	Ta = 25°C			Ta = −40~85°C		UNIT
				MIN.	TYP.	MAX.	MIN.	MAX.	
Output Transition Time	t_{TLH} t_{THL}	—	2.0	—	25	75	—	95	ns
			4.5	—	7	15	—	19	
			6.0	—	6	13	—	16	
Propagation Delay Time	t_{pLH} t_{pHL}	—	2.0	—	27	75	—	95	ns
			4.5	—	8	15	—	19	
			6.0	—	7	13	—	16	
Input Capacitance	C_{IN}	—		—	5	10	—	10	pF
Power Dissipation Capacitance	C_{PD}	(Note 1)		—	19	—	—	—	


Note 1 : C_{PD} is defined as the value of internal equivalent capacitance of IC which is calculated from the operating current consumption without load (refer to Test Circuit).
Average operating current can be obtained by the equation hereunder.

$$I_{CC\,(opr)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC} / 2 \quad \text{(per gate)}$$

OUTLINE DRAWING

SOP8-P-1.27

Unit : mm




Weight : 0.05g (Typ.)

OUTLINE DRAWING

SSOP8-P-0.65

Unit : mm





Weight : 0.02g (Typ.)

OUTLINE DRAWING

SSOP8-P-0.50A

Unit : mm





Weight : 0.01g (Typ.)