
SOT-89 Plastic-Encapsulate Transistors

PXT8050 TRANSISTOR (NPN)

SOT-89



1. BASE
2. COLLECTOR
3. EMITTER

FEATURES

- Compliment to PXT8550

MARKING: Y1

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	25	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current -Continuous	1.5	A
P_C	Collector Power dissipation	0.5	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature	-55~150	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=100uA, I_E=0	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=0.1mA, I_B=0	25			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=100μA, I_C=0	5			V
Collector cut-off current	I_{CBO}	V_{CB}=40V, I_E=0			0.1	μA
Emitter cut-off current	I_{CEO}	V_{CE}=20V, I_E=0			0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V, I_C=0			0.1	μA
DC current gain	$h_{FE(1)}$	V_{CE}=1V, I_C=100mA	85		400	
	$h_{FE(2)}$	V_{CE}=1V, I_C=800mA	40			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=800mA, I_B=80mA			0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=800mA, I_B=80mA			1.2	V
Base-emitter voltage	V_{BE}	V_{CE}=1V, I_C=10mA			1	V
Base-emitter positive favor voltage	V_{BEF}	I_B=1A			1.55	V
Transition frequency	f_T	V_{CE}=10V,I_C=50mA,f=30MHz	100			MHz
output capacitance	C_{ob}	V_{CB}=10V,I_E=0,f=1MHz			15	pF


CLASSIFICATION OF $h_{FE(1)}$

Rank	B	C	D	D3
Range	85-160	120-200	160-300	300-400


Typical Characteristics

PXT8050


Static Characteristic




h_{FE} — I_C




V_{CEsat} — I_C




V_{BEsat} — I_C




I_C — V_{BE}



C_{ob}/C_{ib} — V_{CB}/V_{EB}



f_T — I_C



P_C — T_a

