
Power Transistor(-80V,-1A) 2SB1260

FEATURES

- High breakdown voltage and high current.
  BV_{CEO}=-80V,I_C=-1A
- Good h_{FE}VLinearity.
- Low $V_{CE(sat)}$.
- Complements the 2SD1898.

Lead-free



SOT-89

APPLICATIONS

- Epitaxial planar type PNP silicon transistor

ORDERING INFORMATION

Type No.	Marking	Package Code
2SB1206	ZL	SOT-89

MAXIMUM RATING @ Ta=25℃ unless otherwise specified

Symbol	**Parameter**	**Value**	**Unit**
V_{CBO}	Collector-Base Voltage	-80	V
V_{CEO}	Collector-Emitter Voltage	-80	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current –DC -Pulse	-1 -2	mA
P_D	Total Device Dissipation	500	mW
T_j,T_{stg}	Junction and Storage Temperature	-55 to+150	℃

Power Transistor(-80V,-1A) 2SB1260

ELECTRICAL CHARACTERISTICS @ Ta=25℃ unless otherwise specified

Parameter	Symbol	Test conditions	MIN		MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=-50μA I_E=0	-80			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=-1mA I_B=0	-80			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=-50μA I_C=0	-5			V
Collector cut-off current	I_{CBO}	V_{CB}=-60V I_E=0			-1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=-4V,I_C=0			-1	μA
DC current gain	h_{FE}	V_{CE}=-3V I_C=-100μA	82		390	
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-500mA I_B=-50mA			-0.4	V
Transition frequency	f_T	V_{CE}=-5V,I_C=-50mA, f=30MHz		100		MHz
Output Capacitance	C_{obo}	V_{CB}=-10V f=1.0MHz I_E=0	-	25		pF

TYPICAL CHARACTERISTICS @ Ta=25℃ unless otherwise specified




Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics




Fig.3 DC current gain vs. collector current




Fig.4 Collector-emitter saturation voltage vs. collector current




Fig.5 Gain bandwidth product vs. emitter current





Fig.6 Collector output capacitance vs. collector-base voltage

Power Transistor(-80V,-1A) 2SB1260


PACKAGE OUTLINE

Plastic surface mounted package SOT-89



SOT-89		
Dim	Min	Max
A	4.5	4.7
B	2.3	2.7
C	1.5Typical	
D	0.35	0.55
E	1.4	1.6
F	0.4	0.6
H	1.55	1.75
J	0.4Typical	
K	4.15	4.25
All Dimensions in mm		

SOLDERING FOOTPRINT



Unit:mm

PACKAGE INFORMATION

Device	Package	Shipping
2SB1260	SOT-89	1000/Tape&Reel